Technical data sheet CHRYSO[®]Concrete Stripper

Concrete stripper for equipment

Description

CHRYSO®Concrete Stripper can be used anywhere you find concrete, cement or mortar. It destroys the binder of these materials, making them easy to remove from surfaces by brushing them off.

Advantages

- Formulated from mostly eco-friendly and VOC free etching materials.
- It can be used without damaging the surfaces where cement and concrete is found: coated steel, paints, wiring, plastic, aluminium, chrome, copper, glass.
- It can be left overnight to loosen up the heaviest concrete build up.
- It assists in removing efflorescence from concrete.
- It can be used to clean steel or plastic moulds.
- It can be used to clean severe build up of concrete and cement prior to surface treatments (concrete sealers).

Application guidelines

Use

CHRYSO[®]Concrete Stripper can be used to clean:

- Steel or plastic moulds
- Readymix concrete vehicles
- Mixer drums
- Concrete pumps
- Cement silos
- Cement scales

Physical and chemical properties

- Physical state (25°C): liquid
- pH: 1.5 (±0.3)
- Specific gravity (25°C): >1

Directions

- Depending on the severity of the concrete buildup, CHRYSO®Concrete Stripper can be diluted to a maximum of 1:4 (one part CHRYSO®Concrete Stripper/ four parts water).
- Apply CHRYSO[®]Concrete Stripper by either spraying or brushing onto the surface of the concrete build up.
- Agitate the concrete build up with a brush for several minutes and then rinse. Repeat the process if required.
- You can leave the CHRYSO®Concrete Stripper on the concrete buildup for several minutes or overnight, depending on the severity of the product.

Packaging

- 25 L non-returnable container
- 200 L non-returnable container
- Bulk tanker loads

Storage

If in the original sealed packaging, **CHRYSO® Concrete Stripper** has a shelf life of up to 12 months from the date of manufacturing.

Health and safety

CHRYSO will provide onsite assistance when requested. Refer to the material safety data sheet.

The information contained in this document is given to the best of **CHRYSO**'s knowledge and is the result of extensive testing. However, this document will not under any circumstances be considered as a warranty involving **CHRYSO**'s liability in case of misuse. Tests should be carried out before any use of the product to ensure that the methods and conditions of use of the product are satisfactory. **CHRYSO** specialists are at the disposal of the users in order to help them with any problems encountered.



CHRYSO Southern Africa (Pty) Ltd. Sharecall facility: 0861 CHRYSO Gauteng (head office): 26 Malcom Moodie, Crescent, Jet Park | T: +27(0)11 395 9700 | F: +27(0)11 397 6644 | W: za.chryso.com