

Technical data sheet

CHRYSO® Dem Oleo RT

Release agent - Hydrocarbon oil based,
for roof tiles

Description

CHRYSO®Dem Oleo RT is a Hydrocarbon oil based, delayed release agent for the roof tile industry.

Advantages

- Easy pallet release.
- Ready to use - no additions or dilution required.
- Does not affect the adhesion of subsequent finishes and coatings. Plaster, paint and other coatings may be applied subsequently.
- Made from recycled oil.
- Does not stain or affect the colour of the concrete, when applied correctly.
- Does not modify cement hydration when applied correctly.
- Water repellent and not affected by rain once applied to the pallet.

Application guidelines

Use

- Aluminium rooftile pallets.

Directions

Application

- CHRYSO®Dem Oleo RT is applied either by spray or roller brush applicator on the production line.
- The pallet must be stripped and cleaned of hardened concrete residue, dust, dirt, oil deposits and any form of deleterious substance.

Physical and chemical properties

- Physical state (@ 25 °C): liquid
- Colour: light amber to dark brown
- Specific gravity (@ 25 °C): 0.805 - 0.835
- pH: 5.0 - 6.0
- Viscosity: 8 - 12 secs (Ford # 4 cup)

Coverage


- CHRYSO®Dem Oleo RT needs to be applied as thinly as possible to the entire rooftile pallet surface, by means of an appropriate pressure spray or roller brush applicator.

Precautions

- Avoid insufficient or excessive application. Too much is just as bad as too little.
- Skin irritant - May cause a rash or dry skin
- Safety gloves need to be worn when handling.

Storage

- If in the original sealed packaging, CHRYSO®Dem Oleo RT has a shelf life of up to 24 months from the date of manufacturing
- Avoid storing CHRYSO®Dem Oleo RT in direct sunlight
- In its stored state, CHRYSO®Dem Oleo RT should not come into direct contact with water or rain.
- Should the product freeze, it will recover its properties after thawing and agitating



Technical data sheet

CHRYSO® Dem Oleo RT

Release agent - Hydrocarbon oil based,
for roof tiles

Packaging

- 25 ℓ jerry can
- 200 ℓ drum
- 1000 ℓ flow bin

Health and safety

- CHRYSO®Dem Oleo RT is classified as combustible.
- Safety gloves need to be worn when handling.
- CHRYSO will provide onsite assistance when requested.
- For more information refer to the material safety data sheet.