



## Gripfoot

### Improve grip on smooth surfaces with an abrasive grit finish

- Self-adhesive tapes, cleats or tiles with an abrasive grip surface which helps to improve anti-slip properties.
- A hardwearing and easy to install solution to help prevent slips and trips.
- Available in a range of colours, including a hazard version which provides high visibility in darkness and low light conditions.
- Gripfoot Tape – versatile for floor surfaces, machinery and vehicles.
- Gripfoot Cleats (rectangular) are designed for use on steps and stairs.
- Gripfoot Tiles (square) are ideal for increasing safety on smooth, tiled floors.
- Slip tested to DIN 51130.



### Styles Available



## Parts

Part Number	Size	Colour	Weight
GF120001	25 mm x 18.3 m	Clear	
GF110001	25 mm x 18.3 m	Luminous	
GF010001	25 mm x 18.3 m	Black	
GF010002	50 mm x 18.3 m	Black	

## Technical Specification

<b>Material</b>	Abrasive grit consisting of aluminium oxide bonded to a polymer substrate. Solvent based acrylic emulsion adhesive backing. Product supplied with a moisture resistant release liner.
<b>Surface Finish</b>	Grit
<b>Product Height</b>	1mm ± 0.05mm

Parts

GF120002	50 mm x 18.3 m	Clear	1.45 kg
GF010702	50 mm x 18.3 m	Black/Yellow	0.80 kg
GF010002	50 mm x 18.3 m	Black	0.80 kg
GF020002	50 mm x 18.3 m	Blue	0.80 kg
GF030002	50 mm x 18.3 m	Red	0.80 kg
GF031002	50 mm x 18.3 m	Red/White	0.80 kg
GF040002	50 mm x 18.3 m	Green	0.80 kg
GF070002	50 mm x 18.3 m	Yellow	0.80 kg
GF110002	50 mm x 18.3 m	Luminous	0.80 kg
GF120003	102 mm x 18.3 m	Clear	
GF010003	102 mm x 18.3 m	Black	
GF010004	152 mm x 18.3 m	Black	
GF120004	152 mm x 18.3 m	Clear	
GF120005A	140 mm x 140 mm (10pk) Tiles	Aqua Clear	
GF120005	140 mm x 140 mm (10pk) Tiles	Aqua Clear	
GF130005A	140 mm x 140 mm (10pk) Tiles	Aqua White	
GF010005	140 mm x 140 mm (10pk) Tiles	Black	
GF010006	152 mm x 610 mm (10pk) Cleats	Black	
GF120006	152 mm x 610 mm (10pk) Cleats	Clear	

Technical Specification

Operating Temperature	'-10°C to +60°C
Resistance to Chemicals	N/A
Environmental Resistance	Suitable for indoor environments
UV Resistance	Yes
Typical Applications	Suitable for stairs, ladders, ramps, walkways and vehicles
Installation Method	Pressure sensitive self-adhesive tape
Product Performance	Conforms to Slip Resistance Test EN 13552 Category R13
Country of Origin	Taiwan
Adhesion Strength	2.5Kg/1"
Coating Thickness	0.05mm
Solvent Residue	0.005
Release Force	13Kg/m2