



FLOORWORX GLOSS SEALER

MATERIAL SAFETY DATA SHEET_

DESCRIPTION

FloorworX Gloss Sealer is a durable high gloss water-based acrylic emulsion floor coating and is suitable for use in high traffic areas.

Test	Unit	Specification
Appearance	-	Milky white opaque liquid
pH	-	8,00 - 9,00
Density	g/cm ³	1,00 - 1,05
Non-volatile content	%	23 - 25

FORMULATION

FloorworX Gloss Sealer is formulated on water-based emulsions of acrylic resins and waxes which give safe storage and usage properties. FloorworX Gloss Sealer also has a wide range of special coalescing solvents, plasticizers, levelling and spreading agents, added in small amounts, to give good gloss and economic usage properties. FloorworX Gloss Sealer is formulated to give best results with the minimum of labour.

PROPERTIES

- Self-shining - polishing not necessary.
- Long lasting high gloss finish resists black heel marking.
- Acrylic coating does not collect dirt like wax polishes.
- Reduces slipping and sliding.
- Excellent wear resistance.
- Easy to apply - easy to remove.
- Economical - 1 litre covers 15m².
- Water-based - applicators can be cleaned with water.
- Good protective coating for painted floors.

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016

APPLICATION

Clean floors properly i.e. remove all polishes, oil, dirt, marks etc. Ensure that all detergent is washed off before applying FloorworX Gloss Sealer, as any traces left will destroy the gloss and bond of FloorworX Gloss Sealer. Apply a thin even coating of FloorworX Gloss Sealer. Allow drying and re-applying if necessary. A fresh floor may need 3 applications. FloorworX Gloss Sealer may be applied to a wet floor, but will then take longer to dry and will take up a thinner coat that will necessitate further application.

For extra gloss, buffing is possible but should not be necessary, as correct application of FloorworX Gloss Sealer gives excellent results. When the coatings have become thick from repeated application, it will be necessary to remove using FloorworX Stripper and re-apply to fresh surface.

MAINTENANCE

When necessary, either the floor may be buffed or another coating of FloorworX Gloss Sealer can be applied. FloorworX Spray Buff can be applied to maintain the high gloss should it be required.

THE RECOMMENDATIONS CONTAINED HERE-IN IS BASED ON LABORATORY TESTS AND INFIELD USE EXPERIENCE, AND IS TO THE BEST OF OUR KNOWLEDGE ACCURATE. SINCE TERMS AND CONDITIONS OF ACTUAL USE ARE BEYOND OUR CONTROL, ALL RECOMMENDATIONS ARE MADE WITHOUT WARRANTY, EXPRESS OR IMPLIED.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Product Name:	FloorworX Gloss Sealer
Issue Date:	September 2011
Revision Date:	July 2016
Chemical Product Type:	Emulsions, levelling agents and solvents.
Product Use:	Floor polish.
UN Number:	3082 (Miscellaneous substances).
Supplied by:	FloorworX Africa (Pty) Ltd
Company Location:	32 Steele Street, Steeledale, Johannesburg 2197
Chemical Formula:	Not applicable.
Emergency Contact Number:	+27 11 406 4024 (FloorworX) +27 11 406 4000 (Safic Environmental Solutions)

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016

2. COMPOSITION / INFORMATION ON INGREDIENTS

CAS No.	Hazardous Components	Approximate %	Limit
N/A	None	N/A	N/A
EEC classification	Irritant (Xi), FloorworX Gloss Sealer.		
R Phrases	R36, FloorworX Gloss Sealer.		

3. HAZARDS IDENTIFICATION

Main Hazard:	Irritant.
Fire:	Non-flammable.
Inhalation:	No effect.
Skin contact:	Mild irritant.
Eye contact:	Irritant.
Ingestion:	Nausea, vomiting.

4. FIRST-AID MEASURES

Inhalation	Move patient to fresh air, if there are symptoms.
Skin	Rinse affected area with water.
Eyes	Flush with running water for at least 15 min, irrigate eyes thoroughly while lifting eyelids and rolling eyeballs. If discomfort persists, seek medical attention.
Ingestion	Rinse mouth with water, allow patient as much water as possible. Seek medical attention.

5. FIRE FIGHTING METHODS

Extinguishing Media:	Product non-flammable. Use extinguishing agents for surrounding fire.
Special hazards:	None known.
Protective clothing:	Approved self-contained breathing apparatus should be utilised or equivalent equipment.

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016

6. ACCIDENTAL RELEASE MEASURES

Personal precaution:	Avoid eye and skin contact and wash thoroughly in accidental contact.
Environmental precaution:	Product might be harmful at excessive quantities.
Small spills:	Remove excess with absorbent material and flush residue with plenty of water.
Large spills:	Dyke ahead of liquid spill for later disposal. Prevent the discharge of large amounts of concentrated product into sewerage, and watercourses.

7. HANDLING AND STORAGE

Handling:	Normal handling procedure for polymer based products to minimise personal exposure.
Storage:	Store in a cool dry place. Keep container closed. No special requirements.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workers should have access to an eye wash fountain.

If prolonged or frequent contact is expected, NEOPRENE gloves (Technic 420–supplier–MSA) should be utilised

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque white liquid
pH:	8.00 – 9.00
Density:	1.00 – 1.04 g/cm ³
Solubility (water):	100 %

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Strong acids.
Hazardous decomposition products:	Toxic fumes may be liberated on decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicity:	Acute oral: LD50: 5000 mg/kg, rat. Acute dermal: LD50: 5000 mg/kg, rabbit.
Carcinogenicity:	No evidence of carcinogenic properties.
Mutagenicity:	No evidence of mutagenic effects.
Teratogenicity:	No evidence of teratogenic effects.
Reproductive hazard:	Not expected to impair fertility.

12. ECOLOGICAL INFORMATION

Acute toxicity – fish:	LC50: 10000 mg/l.
Acute toxicity – daphnia:	LC50: 10000 mg/l
Acute toxicity – algae:	IC50: 5000 mg/l.
Biodegradability:	The product degrades into harmless components.
Bio accumulation:	Not expected, as the product is biodegradable.

13. DISPOSAL CONSIDERATIONS

Disposal method:	Dispose as per local agreed government method. The product is non-hazardous.
Disposal of packaging:	Recycle or wash thoroughly and re-use the container.

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016

14. TRANSPORT INFORMATION

UN Number:	3082
Substance identity no. :	FWXS001
ADR/RID class:	Class 9: Irritant liquid
IMDG – packaging group:	III
Marine Pollutant:	No.
IMO/IMDG Classification:	IMDG Class 9 Irritant liquid.
IATA Classification:	Class 9 Irritant liquid.

15. REGULATORY INFORMATION

EC Classification:	Irritant (Xi)
EC Risk phrases:	R36
EC Safety phrases:	S25

16. OTHER INFORMATION

References: SABS 0265: 1999, SABS 0228: 1995, SABS ISO 11014-1: 1994, M.S.D.S.

(Suppliers of raw's)

PLEASE NOTE

The information and recommendations presented on this data sheet are to the best of our knowledge and belief accurate and reliable, but do not constitute a warranty. None of our representatives or agents are authorised to give any guarantee or warranty or make any representation in addition or contrary to the above, and we do not accept liability for claims of any kind for any loss including, without limitation, consequential loss, injury or damage arising from the use of the information or recommendations, or of the products which are subject to the subject matter hereof. These products are sold subject to our standard conditions of sale and tender, copies of which are available on request.

DISCLAIMER

THIS INFORMATION IS BASED ON OUR EXPERTISE AND IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY. FLOORWORX CANNOT ACCEPT LIABILITY FOR ANY DAMAGE, LOSS, OR ACCIDENT CAUSED DIRECTLY OR INDIRECTLY BY THIS PRODUCT.

IT IS THE RESPONSIBILITY OF THE USER TO VERIFY THAT THIS COPY IS THE LATEST VERSION.

DOCUMENT NUMBER: MSDS FWG003 07/2016