# sanitary module for wall-hung WC, 101 cm, with straight connector, water supply connection, bottom



#### Verwendungszwecke / Application Purposes

- · For renovations, conversions and new buildings
- For wall inlets with inlet height 23 cm
- · For replacing wall-hung WCs with close-coupled exposed cisterns
- For connecting Geberit AquaClean Sela
- For connecting Geberit AquaClean Mera
- · For mounting on finished floors
- · For installation in front of solid walls

#### **Eigenschaften / Characteristics**

- Dual flush
- · Compensation of dimensional tolerances possible
- Front cladding made of glass (ESG)
- Height compensation ±1 cm
- Fastening height WC ceramic appliance 35 ± 1 cm
- · Cistern fully insulated against condensation
- Side cladding made of aluminium brushed
- Self-supporting
- · Adjustable flush volume
- · Water supply connection on the left/right possible
- · Water supply connection, bottom
- · Soft-touch buttons for flush actuation and odour extraction
- Orientation light and odour extraction activated when a user approaches
- Orientation light can be set in seven colours
- · User detection range can be set
- · Day/night detection can be set for orientation light
- Odour extraction unit with filtration, integrated in the concealed cistern
- · Odour extraction unit with active carbon filter can be installed without tools
- · Ceramic honeycomb filter for odour neutralisation can be replaced without tools
- · Odour extraction unit automatically switches off after a predefined running time
- · Operation with extra-low voltage, no mains voltage in cistern
- Mains connection with flexible three-wire sheathed cable

# **Technische Daten / Technical Data**

IPX4
100-240 V AC
50-60 Hz
4.1 V DC
5 W
0.1-10 bar
10-1000 kPa
25 °C
6 and 3 l
4.5 / 6 I

# Lieferumfang / Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend 90° made of ABS, ø 50 / 44 mm, 23 x 23 cm
  Sleeve made of EPDM, ø 44 / 55 mm
- Straight connector made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- · 2 threaded rods M12
- · Sound insulation set
- · Female socket for mains connection
- · Power supply unit
- · Fastening material for solid wall

#### Bestelltabelle / Order Table

Art. no.

131.221.SI.1 131.221.SJ.1 131.221.SQ.1 Colour / Surface white glass black glass umber glass

# Zusätzlich zu bestellen / To order additionally

# Zubehör / Accessories

Geberit outlet mounting box

## Interne Datan / Internal Data

Art. no.	Material short text	Sales launch date	GS GS 51 as of	GS 52 as of	Assortment status
131.221.SI.1	MLith Plus WC W-h Al-b bc out-pipe	2014-01-01	50 2016-04-01	2016-07-01	Active
131.221.SJ.1	MLith Plus WC W-h Al-b bc out-pipe	2014-01-01	50 2016-04-01	2016-07-01	Active
131.221.SQ.1	MLith Plus WC W-h Al-b bc out-pipe	2014-01-01	50 2016-04-01	2016-07-01	Active

# Logistik Daten / Logistic Data

Art. no.	PU1[Pc.]	PU1 - L x W x H[mm]	Gross weight[kg]	Net weight[kg]
131.221.SI.1	1	1200 x 600 x 200	29.53	25.08
131.221.SJ.1	1	1200 x 600 x 200	29.48	25.08
131.221.SQ.1	1	1200 x 600 x 200	29.47	24.97