

RAFTER ROLL January 2018

APPLICATIONS



DESCRIPTION

Rafter Roll is a semi-rigid roll of glass mineral wool which is lightweight, flexible, resilient and non-combustible with extra high thermal performance, it is designed for friction fitting between rafters.

PERFORMANCE

Thermal

R-value: $2.24 \text{ to } 5.34 \text{ m}^2\text{K/W}$

Fire

Classification: EUROCLASS A1 to BS EN 13501-1.

with ECOSE

Vapour resistivity

Water vapour resistivity: 5.00MNs/g.m.

BENEFITS

- Excellent sound absorption characteristics
- ✓ Very high thermal performance
- ✓ Provides thermal and acoustic performance
- Quick and easy to install
- Friction fitting allows rafter spacing to be completely filled, thus eliminating air gaps
- ✓ Long roll lengths

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	R-value (m²K/W)	R-value (m²K/W)	Length (m)	Width (mm)	Area per pack (m²)	NRC
200	0.036	5.34	5.55	3.30	1200	3.96	1.00
100	0.032	2.97	3.10	4.00	1200	4.80	1.00
75	0.032	2.24	2.30	5.25	1200	6.30	0.90

All dimensions are nominal





CERTIFICATION























RAFTER ROLL January 2018

ADDITIONAL INFORMATION

Durability

Rafter Roll is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Application

Rafter Roll is designed for insulating between the rafters of pitched roofs in new and existing buildings. It is easy to cut and friction fit, and can be used either as a single or double layer between rafters, or as the first layer of a two layer system in combination with a thermal laminate board.

Standards

Rafter Roll is manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Environmental

Rafter Roll represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

Vapour resistivity

Rafter Roll offers negligible resistance to the passage of water vapour and has a water vapour resistivity of 5.00MNs/g.m.

Handling and storage

Rafter Roll is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Rafter Roll should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens, Merseyside, WA10 3NS. UK

Customer Service (sales): +44 (0)1744 766 767

export.sales@knaufinsulation.com

Technical Support Team: +44 (0) 1744 766 666

technical.uk@knaufinsulation.com

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

