

## AMF TOPIQ® Efficient pro 25 mm



TOPIQ® Efficient pro provides the highest possible class A sound absorption with high humidity resistance and different coating options.

SYSTEM Exposed Grid System, demountable ceiling

Dimensions 600 x 600 mm, 600 x 1200 mm, 600 x 2400 mm

Please note The minimum quantities according to the price list!

Thickness / Weight 25 mm (c. 3,6 kg/m²)

Colour White similar to RAL 9010

Edge details S



## TECHNICAL PERFORMANCE

Reaction to fire A1 as per EN 13501-1

Sound absorption EN ISO 354


 $\alpha_{W}$  = 1.00 as per EN ISO 11654 NRC = 0.95 as per ASTM C 423

Light reflectance For white similar to RAL 9010 glare-free approx. 88%

Sound attenuation  $D_{n,f,w} = 25 \text{ dB as per EN ISO } 10848$ 

Humidity up to 100% relative humidity

Colour White similar to RAL 9010







Knauf AMF GmbH & Co. KG
Elsenthal 15
D-94481 Grafenau
Telefon 08552 / 422-0 - Fax 08552 / 422-32
info@knaufamf.de - www.knaufamf.com

Due to reproduction processes colours shown in this catalogue may differ from the actual product colour. Product selection should always be made from AMF samples. All details and technical information stated in this brochure or other publicity material referring to AMF ceiling systems are based on test reports obtained under laboratory conditions. It is the responsibility of the customer to ensure that this data is suitable for the proposed application. All information provided is based on current technical data. Further relevant test reports, assessments and installation guidelines are available. All system details conform with current standards and are based on the use of AMF products and system components. AMF accepts no liability or responsibility for use of third party components, or for any variations to conditions stipulated in test data. Mixing of production batches is not recommended. All technical data is subject to change without prior notice and is governed by AMF Terms and Conditions of Sales. This catalogue supersedes all previous editions. Errors and omissions excepted. Printing errors excepted.