# <image>

# Cleaning solution for MapePUR sealant guns



# WHERE TO USE

To remove traces of wet **MapePUR** by spraying surfaces, tools, equipment and work clothes with the special cleaning solution and to remove traces of wet foam from inside the feed circuit of sealant guns by screwing the container of cleaning solution to the sealant gun.

# **TECHNICAL CHARACTERISTICS**

**MapePUR Cleaner** is a solvent-based cleaning solution supplied in spray cans.

It may be used either manually, by inserting a cylindrical nozzle into the valve on top of the spray can, or by screwing the spray can to the collar of a **MapePUR Gun Standard** or **Gun Special** sealant gun.

The solvent-based solution contained in the can, which also contains CFC-free gas propellant that is harmless to the ozone layer, is released from the can by pressing on the feed nozzle or by squeezing the trigger of the sealant gun.

### RECOMMENDATIONS

- MapePUR Cleaner is a solvent-based product and must only be used in well-ventilated areas and rooms.
- MapePUR Cleaner is used to remove traces of wet foam only; hardened foam must be removed using mechanical means.
- Before using **MapePUR Cleaner**, make sure it does not harm or damage surfaces it is about to be sprayed on.

### **APPLICATION PROCEDURE**

Shake the can while holding it upside-down (with the feed valve facing the bottom) at least 25 times to mix the contents and propellant together.

Manual use: insert the cylindrical nozzle supplied with the can into the valve on top of the can. Hold the can upside-down at all times while spraying and point the nozzle towards the surface to be cleaned until the traces of foam to be removed have been dissolved/ softened. Remove the traces of foam immediately with a clean rag.

With a sealant gun: screw the can to the **MapePUR Gun Standard** or **Gun Special** sealant gun so that it is attached to the gun in an upside-down position. Squeeze the trigger of the gun and spray for a few seconds until only the cleaning solution comes out of the gun with no traces of foam. Unscrew the can from the sealant gun and place it in an upright position (feed valve at the top). Spray any traces of solution from the sealant gun so that the feed circuit of the gun is completely empty. Dispose of the **MapePUR Cleaner** used for cleaning purposes carefully.

Store **MapePUR Cleaner** in an upright position away from direct sunlight and temperatures above +50°C.

### PACKAGING

500 ml spray can.

### STORAGE

**MapePUR Cleaner** may be stored for 18 months in its original and sealed packaging in a dry and sheltered







Manual use of MapePUR Cleaner

# **TECHNICAL DATA (typical values)**

PRODUCT IDENTITY	
Consistency:	liquid
Colour:	transparent
Flammable:	yes
APPLICATION DATA	
Application temperature:	+5°C to +30°C
Optimum can/contents temperature:	+20°C to +25°C

place with temperatures between +10°C and +25°C.

### SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

### WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

### LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com

