

Siniat System Summary



Siniat Standard Wall -51/F30 A35

Components	System weight (kg/m ²)	Max height (m)	Overall Thickness (mm)	Fire perf (mins)	Acoustic Perf. (R _w -dB)
<ul style="list-style-type: none">• 1x12mm Siniat Standard T/E Plasterboard• 51mm Drywall steel stud• 52mm Drywall steel track• 25mm Drywall Screws• Siniat Drywall jointing compound• Floor and ceiling finishes as per specification	20	3.6	76	30	35

Specifications

Siniat Fixed Partition: 76mm


Supply and install Siniat Fixed Partition from Siniat drywall partitioning system with an overall thickness of 76mm comprising internal framing formed of 51mm Siniat galvanised steel studs fixed at 600mm centers to Siniat galvanised steel top track / aluminium female head section and Siniat galvanised steel floor track, where necessary, any additional galvanised steel stud to form door openings, glazing and other apertures, angles and corners and terminated ends.

The internal steel framing is to be dressed on both sides with 12mm thick Siniat Plasterboard in single layer to suit height, butt jointed and secured to steel studding with 25mm drywall screws at maximum 220mm centers. Joints are to be taped and jointed with Siniat Jointing Compound and Siniat fibatape and prepared for painting.

All external aluminium door frames, glazing frames, ceiling and wall channels and skirting are to be formed of natural anodized / colour anodized / powder coated to specific colour.

Maximum Height: 3600mm

Installation to be in accordance with SABISA (South African Building Interior Systems Association) installation guidelines.



Tel: (+27 11) 389 4500

Email: contactus.mbs@etexgroup.com
www.marleybuildingsystems.co.za