

# Marmoran

The Architects' Choice

## AZTEC

A TEXTURED LOW SHEEN FINISH THAT HIDES SURFACE IMPERFECTIONS AND PROVIDES MAXIMUM PROTECTION



### PRODUCT INFORMATION

- Suitable for interior or exterior use as a protective & decorative coating on either new or previously painted walls that have been properly prepared.
- High build effectively hides surface imperfections.
- Inherent hydrophobic properties offer excellent dirt shedding and water resistance for superior self-cleaning abilities to inhibit fungal growth.
- Accentuate design elements through imaginative paneling and the creation of contrasting bands. We strongly recommend the use tape joints to create paneling and so to avoid dry joints, this is particularly important when applying the product over a large area.
- Tinted to a wide colour range.
- Eco friendly, water based, LOW VOC LEVEL [30 g/L]
- Made to order, supplied ready to use.



### MARMORAN GUARANTEE

**MARMORAN 10 YEAR PRODUCT GUARANTEE** is issued on condition that the system is applied by a Marmoran Licensed Applicator in strict accordance to the full specification and is accepted and signed by the relevant parties. Due to the demand for the highest standard of application and finish, it must be applied by a trained applicator that is skilled and experienced.

SA National Enquiries: 0861 627 266

[www.marmoran.co.za](http://www.marmoran.co.za)

B-BBEE COMPLIANT

© COPYRIGHT 2008:

No part of this document may be reproduced by any means unless express written permission has been granted by MARMORAN (Pty) South Africa.

International enquiries: +27 21 797 4250

Email: [info@marmoran.co.za](mailto:info@marmoran.co.za)

11.12.2019

# Marmoran

The Architects' Choice

## AZTEC

PRODUCT CODE AS031

PRODUCT DATA INFORMATION SHEET

### PRODUCT DESCRIPTION

Marmoran Aztec is a superior high build textured quality coating based on a fine particle size pure acrylic polymer with inherent hydrophobic properties. This hydrophobic nature of the polymer in Marmoran Aztec offers excellent dirt shedding and water resistance for superior self-cleaning abilities to inhibit fungal growth.

### FEATURES & BENEFITS

No primer or top coat required if the substrate is not porous or previously coated. Hydrophobic properties offer excellent dirt shedding and water resistance allowing for superior self-cleaning abilities resulting in excellent fungal resistance.

### TESTED TO NATIONAL & INTERNATIONAL STANDARDS BY THREE INDEPENDENT LABORATORIES

#### TEST STANDARDS

##### SABS 1586:2007

- Controlled water vapour permeability allows the walls to "breathe" to maintain resistance to water ingress and prevent spalling, delamination, algae and dirt retention.
- Exceptional weathering, water repellency and ultraviolet resistant properties
- Ability to withstand high temperatures with no signs of delamination, blistering or loss of adhesion

**SANS 5175** Easily cleaned up to 10,000 scrubs without exhibiting wear or signs or loss of adhesion

**CGR/R+H** Superior quality pure acrylic resin ensures resistance to dirt pickup

**ASTM 4060** Tough & durable with high resistance to abrasion & scuffing

**ASTM G53** UV resistant to prevent excessive chalking, colour change, flaking or peeling

**ISO 1519** Exhibits outstanding flexible qualities, yet hard and durable to withstand the stresses of natural expansion and contraction of the substrate

**ISO 2409** Superior adhesion to all suitably primed substrates

**SABS 5146** Excellent impact resistance and tensile strength

**SABS 1227** Crack bridging properties to span cracks of less than 1 mm

### USES

- Designed for interior or exterior use as a protective and decorative coating for a wide variety of new or previously coated surfaces that have been suitably prepared. This includes cement plasters, concrete, fibre cement, ceiling boards, off shutter concrete, highly porous surfaces, gypsum
- A primer may be required if the substrate is porous or previously painted, or if there is a distinct colour difference between the Marmoran Aztec and the surface to be coated.

### COLOUR

- Available in a wide colour range.

### PACKAGING

Packed in 5, 20 and 200 L containers

### GENERAL CONSIDERATION REGARDING APPLICATION

**SITE SURVEY REPORTS** Site Survey Reports and Records are to be completed prior to product application, during the application and on completion of the project so that the relevant documentation is available for processing the Guarantee.

SA National Enquiries: 0861 627 266

[www.marmoran.co.za](http://www.marmoran.co.za)

B-BBEE COMPLIANT

© COPYRIGHT 2008:

No part of this document may be reproduced by any means unless express written permission has been granted by MARMORAN (Pty) South Africa.

International enquiries: +27 21 797 4250

Email: [info@marmoran.co.za](mailto:info@marmoran.co.za)

11.12.2019

# Marmoran

The Architects' Choice

## AZTEC

### CLIMATIC CONDITIONS

Adequate protection should be provided against rain and sub-zero temperatures for a period of not less than 24 hours after application. The coating should never be applied during adverse weather conditions, or on wet surfaces. Even if the weather seems fit, there may be condensation if the temperature of the substrate is at or below the dew point (temperature at which the atmospheric humidity condenses e.g. as dew) the product should only be applied when the temperature of the substrate is at least 2 deg C above dew point. In hot climates, the coating should be applied during the morning and late afternoon hours and if possible away from direct sunlight. Variations in temperatures will affect drying times.

### APPLICATION CRITERIA

- Please refer to our notes on **BEST PRACTICES FOR SURFACE PREPARATION**.
- **Inspect the substrate:** The plaster substrate must conform to a smooth and even finish. This can be achieved with a fine wood float or we recommend a steel float finish.
- The product must be applied in strict accordance to the Manufacturer's System and Specification.
- Adequate time should be allowed for it to cure [confirm a moisture reading of <15%: this may take from 7-21 days, depending on weather conditions] prior to the application of any specialised, semi-specialised coating or paint.
- **Prepare the substrate** appropriately to ensure that the surface is clean, dry and sound.
- Ensure that the **scaffold** be positioned at a comfortable distance away from the surface so that application technique is not compromised. (400-600mm).
- **Sealing of expansion/control joints:** we recommend the use of sealant compatible with the specified Marmoran product, a suitable Marmoran Primer may then be applied directly over these joints.
- We strongly recommend the use **tape joints** to create paneling and so to **avoid dry joints**.
- **Batch control** it is the responsibility of the contractor to ensure colour consistency. It is recommended that sufficient material to complete the project be ordered where possible to eliminate possible colour variation. Where this is not practical, sufficient material to complete an elevation should be ordered with any excess used as the first coat on the subsequent elevation.
- **Check** spread rates, tools and patterning.
- The product is **supplied ready for use. DO NOT THIN.**

### APPLICATION METHOD

- **If necessary apply** 1 even coat of the appropriate **Marmoran Primer** and allow to cure. We recommend the use of a primer such as Marmoran Universal Primer where the substrate is non porous or dense (i.e. off shutter concrete) followed either by Marmoran RBP Textured Acrylic Primer or Marmoran RLP Textured Acrylic Primer where there is a distinct colour difference between the **Marmoran Aztec** and the surface to be coated.
- **Apply 2 coats Marmoran Aztec** to match the Approved colour & pattern of Marmoran Sample Panel.  
**Rolled Finish:** 2 person technique: the first person spreads the material evenly by **crosshatching with a roller** and second person finishes off by using the **appropriate roller** to obtain the desired textured finish.  
**For a brushed / dragged finish:** 2 person technique: the first person spreads the material evenly by **crosshatching with a roller** and the second person finishes off by using a **block brush** either crosshatching or vertically to obtain the desired textured finish.

# Marmoran

The Architects' Choice

## AZTEC

### SPECIFICATION FOR MARMORAN AZTEC SYSTEM

#### NEW WORK

**Prepare the substrate** appropriately to ensure that the surface is clean, dry and sound. **Inspect the substrate:** The plaster substrate must conform to a smooth and even finish. This can be achieved with a fine wood float or we recommend a steel float finish. Adequate time should be allowed for it to cure [confirm a moisture reading of <15%: this may take from 7-21 days, depending on weather conditions] prior to the application.

**Apply an even coat** of the appropriate **Marmoran Primer** if required.

**Apply 2 coats of Marmoran Aztec** [ASTM E96 Compliant: Controlled Water Vapour Permeability] to match the approved colour & pattern of **Marmoran Sample Panel Reference Number: S/\_\_\_\_\_**.

**This Marmoran Coating System Has A 10 Year International Guarantee Underwritten By A Third Party.**

It is issued on condition that it has been applied by a Marmoran Licensed Applicator in strict accordance to the full specification and is accepted and signed by the relevant parties. Due to the demand for the highest standard of application and finish, it must be applied by a trained applicator that is skilled and experienced.

#### REDECORATION

Prepare the surface by removing all loose and flaking paint, dirt, grease and grime. Make good all cracks and defects and then repair and prime to match the existing surface. Proceed as for new work.

#### PRODUCT DATA

**Composition** Inert Pigments, Fillers and special additives dispersed in a fine particle size pure acrylic resin.

**Solvent Type** Water

**Solids** **Volume** 60% ± 2% **Mass** 75% ± 2%

**VOC LEVEL** 30 g/L [1.84%] white, pastel & medium colours.

**The International GREEN SEAL STANDARD is 150g/L [11.5%] for non-flat coatings.**

**Drying Times** **Surface Dry:** 2 hours **Hard Dry:** 12-16 hours **Over coating:** 12 hours

**@ 25 deg C, 65% RH** Higher temperatures will accelerate the drying times (approximately halved for every 10 deg C increase)

Lower temperatures will retard the drying times (approximately doubled for every 10 deg C decrease)

**Theoretical Spread rate** 2 m<sup>2</sup> / L / coat [2 coats] **Wet Film Thickness:** 500µ per coat **Dry Film Thickness:** 300 µ per coat

This figure is indicative, and subject to applicator skill and substrate type and condition.

Actual spread rates must be determined by the Applicator.

**Shelf life & Storage** 6 - 8 Months in unopened containers.

Store in a cool dry and well ventilated place away from excessive heat or an open flame. Do not allow to freeze.

**Transport** Non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)

**Handling & Safety** This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.

# *Marmoran*

The Architects' Choice

## AZTEC

**Disclaimer** All information contained herein is given in good faith, based on our specialised knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.