

Marmoran

The Architects' Choice

DESIGNER GLAZE

PURE ACRYLIC GLAZE AVAILABLE IN COLOURS



PRODUCT INFORMATION

Marmoran Designer Glaze may be used to over coat many of the Marmoran Coating Systems to create this antique looking lustre as well as providing enhanced protective properties.

FEATURES & BENEFITS

- enhanced protective properties
- controlled Water Vapor Permeability enabling the substrate to "Breathe"
- non-hazardous, non-toxic, and both environmentally and user friendly
- superior washability, detergent resistance and resistance to dirt pickup
- **ECO FRIENDLY - VOC LEVEL 0g/L**

USES

- Designed for interior use, and used to create an aged effect over a variety of Marmoran coatings

COLOUR

- Available in a selected colour range: Antique, Cloud, Gold, Sage & Rose

AVAILABILITY

- Made to order

PACKAGING

- 5 litre containers.



Marmoran

The Architects' Choice

DESIGNER GLAZE

PRODUCT CODE SC004C
INFORMATION SHEET

PRODUCT DATA

GENERAL CONSIDERATION REGARDING APPLICATION BATCH CONTROL

It is the responsibility of the APPLICATOR to ensure colour consistency. It is recommended that sufficient material to complete the project be ordered where possible to eliminate possible colour variation.

APPLICATION

- Apply 2 coats using a brush, rag or sponge to give the required look. Apply in successive thin coats as the application of a thick coat can result in the formation of a milky skin (especially in extreme heat).
- The product is supplied ready for use. Mix with a flat paddle before and during application.
- Spread rate: 8-10 m²/L/ coat.
- The coating should never be applied on wet surfaces. Variations in temperatures will affect drying times.

PRODUCT DATA	
Composition	Adhesion promoted Pure Acrylic Resin, additives & pigments
Solvent Type	Water
Solids	Volume 18% ± 2% Mass 18% ± 2%
VOC LEVEL	0g/L
Drying Times @ 25° C 65% RH	Surface dry: 2 hours Hard Dry: 6-12 hours Over coating time: 12-24 hours. Higher temperatures will accelerate the drying times (± halved for every 10 ° C increase) Lower temperatures will retard the drying times (±doubled for every 10 °C decrease)
Typical Spread Rate	8-10 m ² / L / coat. This figure is indicative, and subject to applicator skill and substrate type and condition. Actual spread rates must therefore be determined by the Applicator.
Shelf Life and Storage	6 - 8 Months in unopened containers. Store in a cool dry and well ventilated place away from excessive heat or open flame. Do not allow to freeze.
Transport	This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)
Handling & Safety	This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.
Disclaimer	All information contained herein is given in good faith, based on our specialized knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.