

Marmoran

The Architects' Choice

MASONRY FILLER

ACRYLIC PASTE FILLER

USED TO FILL IMPERFECTIONS SUCH AS CRACKS AND BLOWHOLES OR TO RECTIFY UNEVEN SURFACES.



PRODUCT INFORMATION

DESCRIPTION

Marmoran Masonry Filler is a premium quality aqueous, ready to use filler for masonry substrates.

USES

- Marmoran Masonry Filler may be used internally and externally to a variety of suitably prepared substrates

FEATURES & BENEFITS

- Is flexible, yet extremely hard and durable.
- Has excellent adhesion to most cementitious substrates.
- Is resistant to saponification under alkaline conditions.
- Has excellent abrasion and impact resistance.
- Has good sanding properties.
- **LOW VOC LEVEL 13 g/L**
- Water based, non toxic, non hazardous, environment and user friendly.



PRODUCT CODE AF001 COLOUR

- Marmoran Masonry Filler is available in a natural white colour.
- Marmoran Masonry Filler is packed in 8 and 32 kg containers.

PRODUCT DATA INFORMATION SHEET

METHOD

- Apply with a spatula, filling knife or a steel trowel.
- Do not apply at a thickness exceeding 3mm, as shrinkage may occur.
- Marmoran Masonry Filler is supplied ready for use.
- Stir well before use, but **DO NOT THIN**.

Marmoran

The Architects' Choice

MASONRY FILLER

REQUIREMENTS

The coating should never be applied during adverse weather conditions, or on wet surfaces. Even if the weather seems fit for painting, there may be condensation if the temperature of the substrate is at or below the dew point (the temperature at which the atmospheric humidity condenses e.g. as dew) Marmoran Masonry Filler should only be applied when the temperature of the substrate is at least 2 deg C above dew point. In hot climates, the coating should be applied during the morning and late afternoon hours and if possible away from direct sunlight. Variations in temperatures will affect drying times. A Marmoran Technical Advisor should be consulted on any matter regarding the use and or application of this product.

PRODUCT DATA

Composition	Acrylic Copolymer resin, additives, fillers.
Solvent Type	Water
Solids	Volume 57% ± 2% Mass 77% ± 2%
Drying Times @ 25 deg C, 65% RH	Surface Dry: 4 hours Hard Dry: 24 hours Over coating: Time 12 hours Higher temperatures will accelerate the drying times (± halved for every 10° C increase) Lower temperatures will retard the drying times (± doubled for every 10° C decrease)
VOC LEVEL	13 g/L 0.64%
Solvent for cleaning	Water
Theoretical Spreading Rates	1 kg / m ² / mm thickness
Shelf Life and Storage	6 - 8 Months in unopened containers. Store in a cool dry and well ventilated place away from excessive heat or open flame. Do not allow to freeze.

TRANSPORT This product is non- hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)

HANDLING & SAFETY This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.

DISCLAIMER All information contained herein is given in good faith, based on our specialised knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.