

Marmoran

The Architects' Choice

SUPAGLAZE GLOSS & SATIN

A CLEAR PROTECTIVE AQUEOUS GLAZE COAT SUITABLE FOR MARMORAN COATING SYSTEMS



PRODUCT DESCRIPTION

Supaglaze is a superior quality clear coating based on a high performance proprietary Acrylic Resin of outstanding quality. Supaglaze may be used to overcoat many of the Marmoran Coating Systems to provide enhanced protective properties. A particular advantage of Supaglaze is its resistance to dirt pickup due to its unique polymeric structure. Supaglaze comes in two finishes: **Gloss & Satin**.

FEATURES & BENEFITS

- enhanced protective properties
- excellent impact and abrasion resistance
- extremely tough and durable
- excellent weather and ultraviolet resistance
- controlled Water Vapour Permeability enabling the substrate to "Breathe"
- non-hazardous, non-toxic and both environmentally and user friendly
- superior wash ability and detergent resistance and resistance to dirt pickup
- **ECO FRIENDLY - VOC LEVEL 0g/L 0.00%**

All Marmoran Products are tested to National and International Standards by independent laboratories.

USES

Designed for interior and exterior (under cover) use as a protective coating over a wide range of Marmoran Coating Systems.

COLOUR & PACKAGING

Available as a single component clear coating in either a Gloss & Satin finish.

Supaglaze Gloss is packed in 5 and 20 L containers.

Supaglaze Satin is packed in 5 and 20 L containers.



SA National Enquiries: 0861 627 266

www.marmoran.co.za

B-BBEE COMPLIANT

© COPYRIGHT 2008:

No part of this document may be reproduced by any means unless express written permission has been granted by MARMORAN (Pty) South Africa.

International enquiries: +27 21 797 4250

Email: info@marmoran.co.za

11.12.2019

Marmoran

The Architects' Choice

SUPAGLAZE

PRODUCT CODE AC009

PRODUCT DATA INFORMATION SHEET

APPLICATION METHOD

- Applied by brush or roller.
- Once the specified Marmoran Wall Coating has fully cured apply 2 coats of Marmoran Supaglaze Glaze to seal. Spread rate: 6-8 m²/L/ coat. Cross hatch to ensure even coverage. Allow to cure between coats.
- **WFT:** 167-125µ per coat **DFT:** 28-21µ per coat

Redecoration of previously applied Marmoran Finish

Wash down surface with low-pressure water jet. Treat any fungal growth with Marmoclean Antifungal Solution. Wash coating with Marmoclean Synergistic Detergent. Rake out any cracks and fill using Marmoran Skimcoat. Repair any delaminated product in panels to match and proceed as for new work.

PRODUCT DATA	
Composition	Adhesion promoted Pure Acrylic Resin.
Solvent Type	Water
Solids	Volume 17% ± 2% Mass 18% ± 2%
VOC LEVEL	0g/L 0.00%
Drying Times @ 25° C 65% RH	Surface dry: 2 hours Hard Dry: 6-12 hours Over coating time: 12-24 hours. Higher temperatures will accelerate the drying times (± halved for every 10 ° C increase) Lower temperatures will retard the drying times (±doubled for every 10 °C decrease)
Typical Spread Rate	6-8 m ² / L / coat. Apply 2 coats, crosshatch to ensure even coverage. This figure is indicative, and subject to applicator skill and substrate type and condition. Actual spread rates must therefore be determined by the Applicator. WFT: 167-125µ per coat DFT: 28-21µ per coat
Shelf Life and Storage	6 - 8 Months in unopened containers. Store in a cool dry and well ventilated place away from excessive heat or open flame. Do not allow to freeze.
TRANSPORT	This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996)
HANDLING & SAFETY	This product is water based and non-toxic. Keep out of reach of children. It does contain chemicals that may be irritants to mammalian tissue. Appropriate protective clothing must be worn. Protect eyes and skin from exposure. If the product is being sprayed, ensure adequate ventilation and ensure the use of proper ventilated masks. Wash spillages immediately with water. Do not induce vomiting if swallowed. Consult a physician if irritation of skin persists or if product is ingested. Gather up environmental spillages, and dispose of in accordance with regulations of the local authorities.
DISCLAIMER	All information contained herein is given in good faith, based on our specialised knowledge and experience. We reserve the right to effect changes to product and specification alike in the interest of product development and improving technology.