



*Tomorrow's Construction Products Today*

7 CLARKE St SOUTH  
ALRODE  
ALBERTON

P.O. BOX 17224  
RANDHART  
1457

**THEORETICAL VOLATILE ORGANIC COMPOUND (VOC) CONTENT**  
**PRODUCT: LEVELiTe F30 Self Levelling Floor Screed Compound**

**1. Abbreviations**

- 1.1 S.G. = Specific Gravity
- 1.2 g/ml = grams/millilitre
- 1.3 g/l = grams/litre

**2. Formulas**

- 2.1 Sum of VOC's in Sealer/Primer formulation = VOC %
- 2.2  $\text{VOC (g/l)} = \text{VOC \%} \times \text{S.G.} \times 10$

- 3.  $\text{S.G. (g/ml)} = 1.00\text{g/ml}$
- 4.  $\text{VOC \%} = 0\%$
- 5.  $\text{VOC (g/l)} = 0 \times 1.00 \times 10 = 0\text{g/l}$

Maximum VOC content (Specified by Green Building Council of South Africa): 50g/l

Peter Funke  
Product Development Manager



Directors: N. Sutherland (Pr Eng..B.Sc.Hon. Chem A.SA Chem1). B.R. Sutherland. M. Krok. W.S. Prusent

phone: 011 864 4918 | fax: 011 864 2123 | 7 Clarke St South, Alrode, RSA, 1451 | [www.iteproducts.co.za](http://www.iteproducts.co.za)