



HETEROGENEOUS



Loft White **9931** w/r 9931
NCS S 0502-G50Y LRV 84.4




Rock Salt **9932** w/r 9932
NCS S 1502-G50Y LRV 64.0




Studio Grey **9933** w/r 9933
NCS S 3000-N LRV 45.2



Urban Chic **9934** w/r 9934
NCS S 5502-B LRV 20.9




Cool Breeze **9936** w/r 9936
NCS S 0515-R80B LRV 70.6




Caramel Blush **9944** w/r 9944
NCS S 2010-Y30R LRV 53.0




Clay Deep **9946** w/r 9946
NCS S 5005-Y20R LRV 24.6



Lilac Essence **9949** w/r 9949
NCS S 1510-R40B LRV 57.2



Nordic Sky **9937** w/r 9937
NCS S 3030-R90B LRV 27.6



Lime Crush **9940** w/r 9940
NCS S 2060-G80Y LRV 38.3



Soft Moss **9942** w/r 9942
NCS S 4040-G70Y LRV 22.0



Woodland Green **9941** w/r 9941
NCS S 3060-G40Y LRV 21.9




Marine Blue **9939** w/r 9939
NCS S 5040-R80B LRV 9.0



Lemon Punch **9947** w/r 9947
NCS S 1080-Y LRV 52.9



Red Beacon **9948** w/r 9948
NCS S 1080-Y80R LRV 18.3



Classic Black **9935** w/r 9935
NCS S 8500-N LRV 4.8

Suitable for both cold and hot welding - see installation details for more information.

w/r = weld rod NCS = Natural Colour System LRV = Light Reflectance Value

bloc

Featuring a single solid colour with a textured emboss, Polyflor Bloc PUR has a 0.70mm pigmented homogeneous PVC wear layer. A high performance, heavy duty heterogeneous sheet floorcovering with a polyurethane reinforcement, Bloc is ideally suited for use within the retail, leisure and commercial sector. The quality of a finished installation of Bloc is dependent upon the preparation of the subfloor which must be smooth. Also the frequency of a regular and well planned maintenance regime should be considered at the outset to ensure the plain floorcovering retains the optimum appearance.



	Gauge	EN 428/ISO 24346	2.0mm
	Wear Layer	EN 429/ISO 24340	0.70mm
	Roll Size	EN 426/ISO 24341	2m x 20m = 40m ²
	Total Weight	EN 430/ISO 23997	2660g/m ²
	General Performance	EN 649 ISO 10582	Conforms Conforms
	Use Area	EN 685/ISO 10874	
	Resistance to Chemicals	EN 423	Excellent chemical resistance
	Reaction to Fire	EN 13501-1 ASTM E648	Class Bfl-S1 Class 1
	Abrasion Resistance	EN 649 EN ISO 10582	Group T Type I
	Slip Resistance*	EN 13893 AS 4586 DIN 51130	Class DS (dry condition) R10 R10
	Indentation Residual	ISO 24343-1 ASTMF970 (Modified)	<0.10mm Static load 750psi
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	Dimensional Stability	EN 434/ISO 23999	<0.40%
	Flexibility	EN 435/ISO 24344	(Method A) Pass 20mm
	Thermal Conductivity	-	Suitable for underfloor heating (max 27°C)
	Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	VOC Emissions	Indoor Air Comfort GOLD FloorScore	Eurofins certified product SCS Certified Reg No: SCS-FS-02034

Environmentally Preferable Flooring - Polyflor **Bloc PUR** achieves a BRE Global A+ rating (Generic) in the Green Guide to Specification in use areas such as retail, education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Polyflor **Bloc PUR** features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring. As with any plain material, the soil hiding properties are less than similarly coloured patterned floors. Higher frequency of maintenance may be required to ensure optimum appearance. Careful consideration should also be given when choosing very light colours in highly trafficked areas. The use of a robust and effective dirt barrier system should be considered early in the specification stage.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

For information and advice regarding handling and installation, adhesives, tailored maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com.

*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.

