

DATA SHEET

WINDOW SYSTEM: **REHAU Tritec 60mm**

WINDOW TYPE: Casement Window, Top Hung / Side Hung - Open Out

GLAZING: 4 - 32mm

U VALUES *:

GLAZING	Ug VALUE (glass)	Uw VALUE (whole window)		
Single Float	Using 5.8	4.20		
Single Low E	Using 3.4	2.81		
Double Standard	Using 3.2	2.70		
Double Low E	Using 2.1	2.1		

^{*} Based on design DT7, standard reinforcing. Calculated using BS EN ISO 10077-1:2000

MAXIMUM SASH SIZES:

Outward Opening Outward Opening Side Hung **Top Hung**

Max Sash size	Maximum *			Maximum *		
Finish	WxH cm	m²	kg	WxH cm	m²	kg
White	90 x 160	1.2	40	120 x 120	1.0	40
White	90 x 160	1.2	40	120 x 120	1.0	40
Coloured/Foiled	90 x 160	1.0	40	120 x 120	1.0	40
Coloured/Foiled	90 x 160	1.0	40	120 x 120	1.0	40

RAL7037

* This is a guide only. Please contact the REHAU Technical Department on 011 201 1300 for detailed information.



COLOURS: The colours below are an indication. For more colour options please contact the

Manufacturer.

GOLDEN OAK

RAL7023

RAL9006 RAL8008 RAL9001

RAL9016

COLOURS:

HARDWARE:

FOIL:

Cockspur and Espagnolette handles are supplied in white, silver, chrome, brown and black, subject to availability. Please confirm colour options with the REHAU Authorised

Partner.