



## TDS TOUGHSEAL UVC

### PRODUCT DATA SHEET

#### Description

A two pack polyurethane sealer, providing excellent UV protection, available in clear or various colours.

#### Uses

- As a UV stable coating.
- The system can be applied over concrete, screeds or asphalt to provide a slip-resistant wearing surface.
- As a concrete coating with high abrasion & wear resistance.

#### Features and Benefits

- Easy to apply
- Light stable, does not yellow.
- Non-slip finish can be tailored to requirements.
- High abrasion resistance.
- Fast installation.
- Exceptional mark & scratch resistance.

#### Coverage

8-10 m<sup>2</sup> per ℓ per coat.

#### Model Specification

Product:	Toughseal UVC
Finish:	Gloss
Thickness:	50 micron D.F.T/coat
Colour:	Various (As per colour chart)

Preparatory work and application in accordance with supplier's instructions.

#### Standard Colour Chart

- Yellow
- Green
- Grey
- Red
- Black
- White
- Clear

---

**Robex S.A. (Pty) Ltd.** Reg: 2002/012975/07

Boksburg (Head Office): 53 Michelson Road, Beyers Park Ext,  
Boksburg, 1459  
P.O. Box 20802, Boksburg, 1460  
T: +27 11 896 9600 F: +27 11 894 2092  
www.robex.co.za



## TDS TOUGHSEAL UVC

Statements made herein regarding the capabilities and performance of this product are expressions of the company's expectations based on field experience. To the best of our knowledge this information is reliable and accurate, however, the buyer must rely on his own skill and judgement in assessing suitability to the application. Robex accepts no liability for losses howsoever incurred arising from the Buyer's use of this product.

All of the information contained within this document remains the property of **Robex SA (Pty) Ltd.**

---