

VAN DYCK

ROMEO





ROMEO

VAN DYCK



While every effort has been made to replicate colours in print, some slight variance may occur. Please refer to sample swatches for accurate colour references.



5 year guarantee
This carpet is guaranteed by Van Dyck Carpets for a period of five years against any latent defect in the manufacturing process. Claims will be treated in accordance with the South African Carpet Manufacturers Standard Claims Policy. However, carpets must have been



Shield RatingThe Shield Rating is a mark of prestige indicating the level of luxury of your carpet with 10 being the highest.



10 year warranty
Van Dyck Carpets (Pty) Ltd offers a 10 year limited warranty against excessive fibre wear



Van Dyck Carpets quality and environmental management systems are certified to SABS 9001 and SABS 14001 respectively. This is your assurance of our commitment to maintain the highest international quality standards.



Color GuardColor guard is one of the most versatile nylon fibre protections on the market. This mark is your assurance that the carpet you have purchased is given durable protection from damages caused by heat and light and prevents it from premature fading.



Torture Tunnel Tested

Every carpet manufactured by Van Dyck Carpets undergoes this unique test during which it is subjected to 75 000 footfalls



Anti-allergenic Carpeting helps trap dust and irritants, which can cause allergies. These can then be



Acoustic Plus
Noise-protection carpet by The Balta Group.

Maintenance

Enhance the performance and appearance of your carpet by following these steps: • Use quality walk off mats. • Vacuum thoroughly and frequently. • Remove spills and marks immediately. • General clean by a SETA Qualified Cleaner.

>> Helpful Hint

Whilst the light colours in the range are extremely attractive, they are high maintenance. They show soil quicker than darker colours and need frequent cleaning. We accept no liability on soiling, as this is maintenance related and not a manufacturing defect.

	TUFTED BROADLOOM, CUT PILE
Pile Fibre:	100% Nylon Imprel® Opal
Backing:	Twin back
Fibre weight:	2000gsm
Total weight:	2700gsm
Total thickness:	12mm
Protective Finish:	Colorguard
Location grade:	Hann Pasidontial
Location grade.	Heavy Residential
Fire rating:	3
Fire rating:	3
Fire rating: Width/Size:	3 4 m Meets requirements of green

Bill of Quantities

ROMEO (colour name), tufted broadloom, cut pile made from 100% Nylon Imprel® Opal by Balta, laid in accordance with the code of practice for the installation of textile floor coverings (SANS 10186).

Satisfaction

Due to dye lot variations and machine settings, actual material may vary from the sample. However this variation is kept within exacting standards as laid down by SANS 1375. Construction of some carpet may involve the occurrence of shift lines across the width of the carpet. Certain light sources shining across the surface may emphasise the effect of shadow lines. These are not a manufacturing defect and will not detract from the carpet's performance.

Colour Variance

Care must be taken when ordering or installing carpeting in individual areas, as carpeting, like all textile products, is subject to shade variation between batches.

CAUTION:

Colour fastness to light: Dyes are selected for their performance and repeatability to commercial standards, but colours can fade when exposed to harsh, direct sunlight. Adequate precautions must be taken to protect the carpet against such exposure to prevent premature fading or damage.

Furniture

Place protectors or carpet off-cuts under furniture to prevent crushing of carpet pile and eventual damage to the backing. Rearrange furniture from time to time to allow pile to recover and change traffic paths. Use carpet protector mats for chairs with castor wheels.