



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090 | info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Beach Sand

(VSBS) Data No 4 – 2016

PRODUCT DESCRIPTION:

A elegant finish which is characterized by the precious metallic reflections and the sandy microns which stand out and give the dark light effect and also a fantastic pearlescent effect. It also exhibits a very pleasant touch and thanks to the special characteristic of Beach Sand guarantees an excellent flexibility during the application and creating elegance in a classic and non classic environment, and also stands out well in modern environments such as public and private places. Beach Sand is non flammable and becomes perfectly washable after 3 weeks after application.

COMPOSITION

Special emulsion acrylic mix of natural and synthetic micas, sand microns, organic and inorganic pigments and additives.

TECHNICAL DATA

- Type: Special Acrylic Emulsion.
- Appearance: Sheen.
- Colors: Available in 5 Standard Colours.
- Solids: 50% – 52% volume.
- Yield: 10 Square Meters / Lt per coat.
- Shelf Life: 6 Months
- Drying Time 12 – 24 Hours at temperature of 25 Degree C
- Dilution: Ready to use.
- Application Brush or Roller

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap roller or brush.
- Thinning: Not recommended.
- Clean up: Tap water
- Spreading rate: 8-10 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: 12 – 24 hours at a temperature of 20 degrees C
- Recoating time: 4-6 hours.
- Requirements: 2 coats.

SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry before painting.
- Previously Painted Surfaces must be sound, clean and dry before painting.

After all surfaces are sound, clean and dry apply one coat of Versus Universal Undercoat as a tie coat. Other areas that have chalked and are powdery should be well sanded and sealed with Versus Plaster Primer.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 5 litres.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.