



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090 | info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Glitter Paint (VGP) Data Sheet no 3-2018

PRODUCT DESCRIPTION:

A high performance satin/mid sheen Glitter flexible wall paint.

Meets the requirements of SABS 1586 Grade 1.

USES:

- Ideal for interior and exterior high traffic areas that need a highly washable and durable coating – plaster, hardboard and fiber cement.
- Suitable for application to correctly primed metal and wooden surfaces.

FEATURES:

- Water based: Low odor and easy cleaning.
- Highly durable and UV resistant for South African harsh climate.
- Quick drying.
- Excellent wear resistance properties.
- Washable: Meets the requirements of the SABS and ASTM scrub resistant test methods.
- Mar and scratch resistant.
- Good color stability.
- Non Yellowing: Unlike alkyd based paints whites and colors will not yellow.
- Water and steam resistant.
- Excellent resistance to spatter.
- Excellent adhesion, good flow and excellent opacity.
- If correctly applied to a properly prepared substrate the product has a life expectancy of 7-10 years, possibly longer.
- Very low levels of VOC. 20g/Lt.

PRODUCT INFORMATION:

- Type: Pure Acrylic.
- Appearance: Sheen.
- Colors: Available in a range of popular ready mixed colors.
- Solids: 50% – 52% volume.
- Density: 1.2 – 1.4.
- Recommended Dry Film Thickness: 35µm – 45 µm.
- Viscosity at 25°C: 95 – 100 Krebs µ.
- Flash Point: Non-flammable.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap roller, brush or airless spray.
- Thinning: Not recommended. Thinning reduces the opacity. For spraying you can thin up to 10% with clean water.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.

- Clean up: Tap water
- Spreading rate: 8-10 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry ½ – 1 hour. Hard dry 3 hours at 25 degrees.
- Recoating time: 4-6 hours.
- Requirements: 2 coats.

SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry before painting.
- Concrete and cement should be filled with Versus Versafill.
- Gypsum Plaster should be primed with Versus Plaster Primer.
- Fibre Cement ceiling boards: the bare metal areas (nail heads) should be primed with Versus Steel Primer.
- Wooden surfaces should be primed with Versus Pink Wood primer.
- Galvanized Iron should be cleaned first with Versus Galvanized Iron Cleaner until a water break free surface has been achieved. Thereafter prime with Versus Galvanized Iron Primer and followed with Versus Universal Undercoat.
- Rusted Metals should be wire brushed or sanded to remove all rust. Prime with Versus Steel Primer. Thereafter apply Versus Universal Undercoat.
- PVC gutters and downpipes should be degreased and then abraded with fine sandpaper and then the topcoat can be applied directly.
- Previously Painted Surfaces must be sound, clean and dry before painting.

After all surfaces are sound, clean and dry apply one coat of Versus Universal Undercoat as a tie coat. Other areas that have chalked and are powdery should be well sanded and sealed with Versus Plaster Primer.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 5 litres and 20 litres

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare metal surfaces.
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces.
- Do not apply before 9am and after 4pm in the winter.
- Do not apply exterior if it looks like rain will occur within 4-6 hours of application. Do not apply direct to chalky or friable surfaces.