



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Status Matt

Data Sheet no 28/2018

PRODUCT DESCRIPTION:

- A high performance, matt superior quality acrylic emulsion for interior and exterior high traffic areas.
- Meets the requirements of SABS 1586 Grade 1.

USES:

- Final coats to interior and exterior sound plaster, hardboard and fiber cement.
- Application to correctly primed metal and wood surfaces.

FEATURES:

- Water based: Low odor and easy cleaning.
- Durability: Highly durable and UV resistant for the harsh South African climate.
- Adhesion: Excellent adhesion if applied to sound surfaces.
- Low VOC: This product contains no toxic substances and very low levels of VOC (EU Regulations)
- Life Expectancy: 7-10 years on condition preparation and application are done properly.

PRODUCT INFORMATION:

- Type: 100% Acrylic.
- Appearance: Matt.
- Colors: White and arrange of 16 standard colors. Pastel, Medium and Deep tone. Colors can be tinted on request.
- Solids: 45% – 50%. Bx Mass
- Density: 1.2 – 1.25KG/L.
- Viscosity: at 25°C 105-110 Kress
- Flash Point: Nonflammable.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 5 litres and 20 litres

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Brush, roller or Airless Spray.
- Thinning: Not recommended, but tap water if required. Thinning reduces the opacity. (Hiding power).
- Clean up: Tap water
- Spreading rate: 6-12 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather.
- Minimum temp 8°C.
- Drying time: Touch dry ½ – 1 hour.
- Recoating time: 4-6 hours.
- Requirements: 2 coats.

SURFACE PREPARATION:

- All Surfaces must be sound, clean and dry before painting.
- New concrete surfaces: 1 coat of Versus Plaster Primer.
- New or weathered fiber cement: 1 coat Versus Bonding Liquid.
- New raw plaster: 1 coat Versus Plaster Primer.
- Rusted metal areas need to be cleaned back to bright metal and spot primed with Versus Steel Primer.
- New metal surfaces need to be abrasively de-greased to remove the manufacturers grease protective layer this process is repeated until the surface is water break free. After drying the whole substrate is coated with Versus Steel Primer.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare metal surfaces.
- Drying times will be extended during wet or cold weather conditions.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.