



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Versatex Textured Acrylic Coating (VVT) Data sheet no 5-2015

PRODUCT DESCRIPTION:

A fine matt textured paint which provides high cover and is very flexible for interior and exterior use.

USES:

- For application as a finishing coat for exterior new or previously painted cement plaster, concrete and fiber cement.
- Particularly recommended to obliterate hairline cracks in cement plaster.
- For areas prone to mould growth.
- Ideal for high traffic areas or areas that may require frequent washing.

FEATURES:

- Water based: Easy to apply and easy clean up.
- Water resistance: Surpasses the SABS 0400:1900 Code of Practice rain penetration test over a 24 hour period.
- It contains mould inhibitors providing protection against mould regrowth.
- Excellent weather resistance.
- UV Resistant.
- Excellent exterior durability.
- Good color stability.
- Very good opacity, and alkali resistance, stain resistance and wash ability.-

PRODUCT INFORMATION:

- Type: Pure Acrylic.
- Appearance: Matt Texture.
- Colors: White and a range of 16 standard colors. Pastel and Medium colors can be tinted on request.
- Solids: 54 – 56% by volume.
- Density: 1.27 – 1.35 kg/l.
- Viscosity at 25°C: 120 -120.
- Flash Point: Non-flammable.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Sheepskin roller or brush. For a more pronounced texture use a honeycomb sponge roller.
- Thinning: Not recommended, but tap water if required (First coat). Thinning reduces the

opacity as well as crack bridging properties.

- Clean up: Tap water
- Spreading rate: 3 – 5 m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: ½ – 1 hour at 25 degrees. Hard dry 4 hours at 25°C.
- Requirements: 2 coats.

SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry before painting.
- Concrete and cement: Apply 2 coats direct on the surface. The first coat can be thinned to a maximum of 10% water.
- Fibre Cement: Apply 2 coats. The 1st coat may be thinned with 10% clean water to aid penetration.
- PVC gutters and downpipes: Should be abraded with fine sandpaper before the topcoat can be applied.
- Previously Painted Surfaces must be sound (no chalking), clean and dry before painting.

After all surfaces are sound, clean and dry apply 2 coats of Versus Textured Paint W.G.

Enamel surfaces must be sanded first and then a coat of Versus Universal Undercoat must be applied before applying the topcoat.

STORAGE:

Keep containers properly sealed.
Store away from direct heat, sun and severe cold.

PACKAGING:

20 Litres.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Do not apply directly to bare metal surfaces.
- Do not paint in wet or cold weather. (Minimum 8°C.)
- Drying times will be extended during wet or cold weather conditions.
- Do not apply direct to chalky or friable surfaces. Apply a penetrating coat of Versus Bonding Liquid or Versaprime Plaster Primer.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.