



weber.cote Brush Coat

A cement-based textured decorative
interior/exterior wall coating



About this product

weber.cote Brush Coat is a cement-based, coloured, waterproof, textured finish for interior and exterior walls. Applied by block-brush. Produced from carefully selected raw materials for consistency of product, it only requires the addition of water on site.

Technical services

Weber has a team of experienced advisors available to provide technical support. Technical helpline: 08600 **Weber** (93237) or visit www.weber-tylon.co.za

Packaging

weber.cote Brush Coat is supplied in 20 kg paper bags.

Coverage

Coverage is approximately 7 to 10m² per bag.

Use

Provides a durable, coloured, waterproof coating for brick- or block-work in one coat.

Features and benefits

- Waterproof
- Integrally coloured for low maintenance
- Single coat application
- Available in a range of colours
- Quality assured raw materials
- Exceptional and consistent quality
- Backed by superior technical support

Suitable surfaces

Flush brick-work or block-work and scratched cement plaster. Not suitable for previously painted surfaces.

Good practice

Do not apply:

- If frost is forecast within 24 hours of use
- In damp/wet conditions
- In temperatures below 5°C or above 30°C
- On elevations in direct sunlight or where the substrate is hot

To ensure colour consistency, the material required to complete the job should be of the same batch number.

Surface preparation

The surface onto which **weber.cote Brush Coat** will be applied:

- Must be cured for a minimum of 28 days
- Must be sound, clean and free of any material which may impair adhesion
- Must be true in plane, hard and slightly rough to form a mechanical key

Masking

Mask all areas where there is a risk of splashing and staining and where straight edges are required. Masking tape must be removed before the material has dried.

Application

Filling holes and indentations

Mix 4 volumes of **weber.cote Brush Coat** and 1 volume of water to a paste. Use this mix to fill any holes or indentations in the surface. Scrape flush with the surface and leave to dry overnight.

Mixing

- Combine 3 volumes of **weber.cote Brush Coat** with 1 volume of water.
- Stir thoroughly.
- A small amount of water may be added if necessary.

Application method

The surface should be dry when application starts.

- Wet the brush and shake off excess water.
- Dip the brush in the mixture and brush the wall liberally. Make sure to fill small holes and indentations.
- Coat the entire wall in one operation to avoid dry joints. Do not stop and start. Do not patch.
- Leave overnight to air cure.

Note: A second coat may be applied if required and should be cured in the same way.

Curing

Wet the coated walls 3 times during the next day using clean water.

Storage and shelf life

When stored, unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

Safety instructions

Contains cement, which is alkaline when wet and can cause skin irritation. Use eye protection and gloves and avoid prolonged skin contact. Avoid inhalation of dust. Wash skin contamination away with warm soapy water. Remove splashes to the eyes by prolonged irrigation and consult a doctor. Do not ingest.

Guarantee

We agree that **Weber** products meet the product specifications and will be free from any defect. Any guarantee with regard to the performance of Weber products will be subject to its professional and practical application of Weber products in accordance with our instructions and specifications. However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain advice. Should our product prove defective, we undertake to replace any defective material. This guarantee will fall away in the event of Weber products being contaminated by the addition of sand, cement or substance other than recommended by us.