



reddot design award
winner 2018



Blum-Awards
www.blum.com/award



AVENTOS HK top

Webcode
ID20280 ◀

for stay lifts

- Ideal for cabinet heights up to 600 mm in wall cabinets
- Suitable for wall cabinets with cornice or crown mouldings
- Easy opening, variable stop and silent and effortless closing thanks to the integrated BLUMOTION dampening
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Fast assembly and removal of the front using CLIP technology

Product overview

Blum AVENTOS HK top for stay lifts. Compact stay lift fitting with internal minimum depth of 187 mm. Made in Austria. For thin fronts from 8 mm, wooden, wide/narrow alu frame fronts, mitred and rebated applications. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using infinitely variable lift mechanism adjustment. Convenient lift mechanism adjustment from the front. High stability even for wide fronts. Integrated closing dampening. Integrated safety feature prevents the lever from being opened unintentionally. Integrated, infinitely variable opening angle stop. Simple, tool-free fast installation of the front using clip-on assembly method. Lift mechanism can be attached to the cabinet side before assembly. No parts projecting beyond the cabinet side. Can be combined with a mechanical or electric opening support system. No hinges required. For cabinet heights from 205 mm to 600 mm.

Convenient three-dimensional front adjustment using Torx screws: Height ± 2 mm, Side ± 2 mm, Depth ± 2 mm.

Straightforward, minimalist cover cap made of nylon in light grey, silk white or dark grey

- a) silk white
- b) light grey
- c) Dark grey

Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.

Equipment options

- ▶ ID20284 SERVO-DRIVE for AVENTOS HK top
- ▶ ID20153 TIP-ON for AVENTOS stay lifts



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue