CAPE BRICK Est. 1931

CREATING A SUSTAINABLE FUTURE TOGETHER

BRICK BY BRICK

T (021) 690 2020
E sales@capebrick.co.za
W www.capebrick.co.za

PRODUCT DATA SHEET

PRODUCT NAME: **MA190 Rockface (Full block / Half block)**
PRODUCT CATEGORY: **BLOCKS**
ENVIRONMENTAL RATING: **CONTAINS UP TO 60% RECYCLED CONTENT**
DIMENSIONS (LxWxH): **390mm/190mm X 190mm X 190mm**
COMPRESSIVE STRENGTH: **7 Mpa (Net area)**
MASS: **17.50 kg / 10.00 Kg**
NO / M²: **12 / 24**
NO / PALLET: **72 / 144**
CEMENT: **Pretoria Portland Cement (SA)**

Earth Brown

Grey

Sandstone

Charcoal



Full size block

Half block
Corner module

PRODUCT DESCRIPTION

A 7mpa strength rockface finish MA190 block and corner/half block designed for all masonry walling where an aesthetic finish is required. Available in 4 colours, being concrete grey, charcoal, sandstone and earth brown. Can also be incorporated into R12 rockface finish retaining wall and step block designs.

CAPE BRICK
cnrWeltevreden & Old Landsdowne Road, Philippi
www.capebrick.co.za



Colour representations are approximate and are not a guarantee of the exact appearance on site due to raw material and production variances

CHRYSO®Finisol Brut

Concrete sealer forexposed aggregate concrete

CHRYSO®FiniSol Brut is a water-based concrete sealer designed to protect aesthetic concrete, especially on concrete at early ages (12 to 24 hours after concrete casting). This product is particularly adapted to protect exposed aggregate concrete, on which it can be applied immediately after the wash out of the surface retarder.

CHRYSO®FiniSol Brut has a tracing effect that helps to see the treated areas and to optimize the dosage. The white aspect totally disappears when drying.

CHRYSO®FiniSol Brut is particularly appropriate to protect exposed aggregate concrete. It can be immediately applied after the washing away of the top-surface retarder.

CHRYSO®FiniSol Brut is a film-forming sealer that reduces stains and thanks to its hydrophobic and oleophobic functions, protects against water, oils and dust.

CHRYSO®FiniSol Brut improves surface toughness, abrasion and wear resistance (ISO 11-998 and ASTM D24-56) and reduces also the appearance of efflorescences.

CHRYSO®FiniSol Brut does not modify the aspect and the colour of the substrate on which it is applied. It is not yellowing in the length (Accelerated ageing test - NF EN ISO 11-507).

Its water based formulation makes it safe for users.

CHRYSO®FiniSol Brut is ready-to-use and can be applied by brush, roller or spray for both interior and exterior applications.

Apply CHRYSO®FiniSol Brut on “wet” substrate, free of any water excess (puddles...).
Apply in a uniform manner without any run-downs or puddles.

Indicative characteristics

- Nature: liquid
- Colour: White
- Specific gravity: 1,020
- pH: 8,00
- Freezing point: -1 °C
- COV inférieur à (Cat A – I de la Directive n° 2004-42/CE): 55 g/L
- Shelf life: 12 months

Domains of application

- Exposed aggregate concrete
- Aesthetic concrete
- Street furniture
- Precast elements
- Exposed aggregate roadworks and slabs

Precautions

Protect from frost.
Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

CHRYSO®FiniSol Brut must be applied on clean substrates, free of any water excess. In case of excess, brush them away.
Do not apply when it is wet or when temperatures are below 10 °C.

Method of use

Consumption: 150 to 250 g/m²

CHRYSO®FiniSol Brut dosage depends on the porosity of the surface to be treated. The average coverage for one coat is 1 litre for 5m².