





COBAwash®

Practical, machine washable

- A real asset in floor protection for domestic and commercial use.
- Easy care, smaller sizes* can be washed in a domestic washing machine. (All sizes can be washed in an industrial washing machine.)
- Tufted nylon/polyester carpet pile retains up to 3.5 litres/m2 of moisture.
- Also traps up to 800g of debris/dry dust.
- Features a robust nitrile 'gripper' backing.
- Bleach / fade resistant – 11 year warranty against significant colour loss.
- Pile material: nylon/polyester.
- Backing: Features a robust nitrile 'gripper' backing.




Styles Available



Black/Red



Black/Brown



Black/Blue



Black/Steel

Parts

Part Number	Size	Colour	Weight
LM010201	0.6m x 0.85m	Black/Blue	1.25 kg
LM010301	0.6m x 0.85m	Black/Red	1.25 kg
LM010501	0.6m x 0.85m	Black/Brown	1.25 kg
LM010601	0.6m x 0.85m	Black/Steel	1.25 kg
LM010202	0.85m x 1.5m	Black/Blue	3.00 kg
LM010302	0.85m x 1.5m	Black/Red	3.00 kg
LM010502	0.85m x 1.5m	Black/Brown	3.00 kg
LM010602	0.85m x 1.5m	Black/Steel	3.00 kg
LM010203	1.15m x 1.75m	Black/Blue	4.75 kg

Technical Specification

Material	Surface dyed washable nylon
Backing	Nitrile
Product Height	8mm
Product Weight	2.3Kg/m2
Operating Temperature	0°C to 60°C
Resistance to Chemicals	Rubber is resistant to many chemicals, alkalis, detergents and general industrial chemicals. Rubber may swell in polar solvents.

Parts

LM010303	1.15m x 1.75m	Black/Red	4.75 kg
LM010503	1.15m x 1.75m	Black/Brown	4.75 kg
LM010603	1.15m x 1.75m	Black/Steel	4.75 kg
LM010608	0.9m x 3m	Black/Grey	

Technical Specification

Environmental Resistance	Primarily intended for indoor use
UV Resistance	Yes
Typical Applications	Dust control entrance mat, ideally placed in high traffic, high profile places. Entrances, lobbies, etc.
Installation Method	Loose lay
Cleaning Method	0.6m x 0.85m and 0.85m x 1.2m can be washed in standard domestic washing machines. All other sizes can be laundered in commercial washing machines.
Flame Retardancy	BS 4790:1987 (Hot metal nut test) - low radius of effects of ignition/ EN 13501-1 Bfl-s1.
Country of Origin	UK
Guarantee	2 year against manufacturing defects. 11 year against colour loss, subject to washing instructions being adhered too.

Get in touch | To order FREE samples or arrange a site visit please call +27 (0) 11 452 7961 or email sales@cobaafrika.com