



Orthomat®

The original fatigue fighter




- Pebbled 'textured' surface.
- Available as Orthomat® Safety with bright yellow bevelled edge borders.
- Conforms to Slip Resistance Test EN13552 (Category R10).
- Fire tested to DIN54332 (B2) part of DIN4102.



Styles Available



Standard



Safety

Parts

Part Number	Size	Colour	Weight
-------------	------	--------	--------

Technical Specification

Material	Virgin Closed Cell PVC (Foam)
----------	-------------------------------

Parts

AF010004	0.45m x 0.9m	Black
AF010003	0,9m x 18.3m	Black
AF010003C	0.9m x linear meter	Black
AF010701	0.6m x 0.9m	Safety
AF010702	0.9m x 1.5m	Safety
AF010703	0.9m x 18.3m	Safety
AF010703C	0.9m x linear meter	Safety

Technical Specification

Surface Finish	Pebble
Product Height	9mm
Roll Length	18.3m
Size of Safety Border	100mm
Operating Temperature	0°C to +60°C
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Production lines, assembly areas, packing stations, workbenches.
Installation Method	Loose lay
Cleaning Method	Brush/Mop the top surface
Product Performance	Conforms to Slip Resistance Test EN 13552 (Category R10).
Flame Retardancy	Fire Tested to DIN 54332 (B2) part of DIN 4102.
Country of Origin	China
Guarantee	1 year guarantee when used in a dry environment
Permanent Adhesive Recommendation	F44
Release Adhesive Recommendation	F41
Heavy-Duty / Wet Area Adhesive Recommendation	F74, F81, F84