



Bubblemat

Hard wearing rubber mat



- Hard wearing rubber mat
- Raised surface stimulates blood circulation on foot movement.
- Safety bevelled edging as standard.







Parts

Part Number	Size	Colour	Weight
BF010001	0.6m x 0.9m (edged all round)	Black	6.35 kg
BF010002	0.9m x 1.2m (edged all round)	Black	10.50 kg

Technical Specification

Material	(100% natural rubber) and other approved rubber chemicals used in rubber industry.	
Surface Finish	Bubble shaped	
Product Height	14mm	
Operating Temperature	'-30°C to +50°	
Resistance to Chemicals	Resistant to water and most mild acids	
Environmental Resistance	Use predominantly in dry areas	
Typical Applications	Ideal for manufacturing production areas where employees are standing in static positions	
Installation Method	Loose Lay	

Technical Specification

	ub the mats.	
chemicals. Do not mechanically scru		
mats. Do not use steam or degrease	ers or caustic	
results use a mild detergent (pH 4.0-	9.0) to clean the	
Method remove the dirt and debris on the ma	remove the dirt and debris on the mats. For best	
Cleaning Use a high pressure hose (not excee	Use a high pressure hose (not exceeding 60psi) to	

Origin Sri Lanka

Get in touch | To order FREE samples or arrange a site visit please call +27 (0) 11 452 7961 or email sales@coba