

Renown

BMI Coverland Renown roof tile, a refined, chiselled, sophisticated and low-profiled tile, designed to blend unobtrusively into any environment with a more contemporary feel and comply with SANS 542 for concrete roof tiles when used with BMI Coverland fittings to suit the design criteria.

TILE FINISHES

Through Colour

A single-shaded base colour throughout the roof tile displays a distinct surface.

TECHNICAL DATA

Overall size of tile (mm)	420 x 330
Approx mass per tile (kg)	4.4
Linear cover per tile (mm)	300

STRUCTURAL DATA

The roof structure specifications should comply with the regulations in your area.

Minimum pitch requirements	17° to 25°	26° and over
Rafter Centres	Up to 760 mm 38 x 38 Batten	Up to 950 mm 38 x 50 mm Batten on edge
Headlap (mm)	100	75
Batten Centres (mm)	320	345
Batten per m ² (m)	3.13*	2.9*
Number of tiles per m ²	10.42	9.66
Approx mass of tile m ² (kg)	46	43
Laying application	Straight bond	Straight bond
Undertile Membrane/ Radenshield™	Mandatory	Recommended
recommended at all pitches		

*No allowance for wastage.

PACKAGING

Number of tiles per pallet	210
----------------------------	-----



Cost Effective¹




Aesthetics



Durable

Technical information



Colours



DISCLAIMER: The colour of these illustrations may vary due to the printing process. BMI Coverland recommends that you view actual tile samples before reaching a purchase decision. ¹Based on comparative research done on roof tiles vs metal roof installations.



STRUCTURAL AND ENGINEER SPECIFICATIONS

BMI Coverland Renown, to comply with SANS 542 for concrete roof tiles, and BMI Coverland fittings to suit the design criteria secured with BMI Coverland non-corrodible clout nails, as supplied by BMI Coverland, long enough to penetrate the battens to 2/3 of its depth. BMI Coverland Concrete Roof Tiles are to be nailed and/or clipped to resist wind uplift in accordance with the existing SABS codes of practise and recommended fixing specifications for your area. BMI Coverland Concrete Renown tiles must be laid in a straight bond.

BMI Coverland Concrete Roof Tiles at a minimum of 17° degrees pitch for 38x38mm timber battens, spaced at a minimum of 320mm and a maximum of 345mm c/c on 38x114mm SAP grade 4 timber rafter and 38x152mm SAP grade 4 tie beam maximum specification at 900mm c/c as per Engineer specification on 38x114mm SAP grade 4 timber wall plate with a BMI Coverland Single-Sided or Double-Sided Residential Radenshield, to be nailed to the rafters with BMI Coverland non-corrodible Clout nails, and trusses to comply with SABS 563 softwood structural and Engineers specifications and battens to comply with SABS 653 softwood battens and brandering – battens joints must meet halfway across the top face of a rafter and batten nails must be BMI Coverland non-corrodible 3,35mm in diameter long enough to penetrate the rafter to a depth of 55mm.

SECURE YOUR ROOF

BMI Coverland offers quick and easy to install storm clips and non-corrodible clout nails, long enough to penetrate the battens to 2/3 of its depth, for fast and professional securing of concrete tiles. Our clips match the respective tile profiles exactly to provide reliable and durable protection against wind upliftment and slipping in accordance with the existing SABS codes of practise and recommended fixing specifications for you area with an added security benefit against intruders entering the roof.

See our Technical Guide for your area's specifications.

INTENSE PRODUCT TESTING

Our roofing products are tested in a wind tunnel unique to the industry, simulating wind and rain conditions found in a wide range of climate zones worldwide, including situations which typically arise only every 50 years. BMI only releases the new roofing materials when all trials as well as several hardness and long-term ageing tests have been successful.

GUARANTEE

A lot can change in 30 years, but your roof doesn't have to. With a track record of just over 70 years and the backing of BMI Technical Centre, we are proud to introduce our **30 Year Roof Tile Concrete Guarantee**.

Your roof is your protection from the elements, your shelter and with our guarantee, your peace of mind. Our concrete tiles are guaranteed against the event of damage to the weather resistance of the product resulting from a manufacturing defect. In the unlikely event that damage occurs, BMI Coverland will repair the affected product for the lifetime of the guarantee.



EFFLORESCENCE

Efflorescence, often referred to as "lime bloom", is a natural phenomenon and is found in products containing cement. It is a white deposit which appears on the surface of all concrete based products. Efflorescence is a temporary condition, and does not affect the functional properties of the product. Wind and rain will gradually remove the deposit and the true colour of the tile will be restored.

#becauseitsneverjustarroof

GUARANTEE DISCLAIMER: T's & C's apply. For more information please contact your sales representative or email us.