

Geberit DuoFresh module with manual actuation, for Sigma concealed cistern 12 cm



Application purposes

- For Geberit Sigma concealed cisterns 12 cm
- For direct odour extraction from WC ceramic appliances
- For Geberit actuator plates Sigma01
- For Geberit actuator plates Sigma10
- For Geberit actuator plates Sigma20
- For Geberit actuator plates Sigma21
- For Geberit actuator plates Sigma30
- For Geberit actuator plates Sigma50

Characteristics

- Front actuation
- Odour extraction unit with filtration, integrated in the concealed cistern
- Extraction unit can be mounted without tools
- Odour extraction unit can be activated with Geberit Home App
- Odour neutralisation with ceramic honeycomb filter

Technical data

Protection class	III
Protection degree	IPX4
Operating voltage	12 V DC
Power consumption	7 W
Power consumption standby	≤ 0.5 W

Scope of delivery

- Mounting frame with swivelling mechanism
- Protection plate
- Extraction unit with radial fan
- Cable connection with plug
- Ceramic honeycomb filter
- Moisture protection for conduit pipe

To order additionally

- Power supply unit 230 V / 12 V / 50 Hz, for Geberit DuoFresh module, for outlet mounting box

Art. no.	Surface / colour	
115.995.BZ.1	anthracite grey RAL 7016	NEW
115.995.21.1	bright chrome-plated	NEW

Accessories

- Geberit combination outlet mounting box
- installation set with flush-mounting box, for Geberit DuoFresh module



- Switch for activating and deactivating odour extraction must be provided by the customer