



Gunnebo ARMOUR Plus

Multi-purpose Steel Security Doors

The Gunnebo ARMOUR Plus range of security doors offers multiple levels of protection for external and back of house applications. Highly resistant security materials and tried and tested design all combine to protect against ballistic and manual attacks. Doors can be supplied with optional features to include additional blast and fire protection

- A powder coated finish to door and frame is provided as standard. Alternative finishes can be accommodated
 - Doors are available with or without a vision panel. Vision panels are made to match the resistance level of the door
 - The door is tested to meet SABS ballistic standards of G1-G3 (Equivalent FB2-FB7 EN 1522)
 - Bespoke sizes are available including single as well as double leaf doors. The door comes pre-fitted in a matching ballistic frame. The frame is pre-drilled for fast, hassle free installation in a fully finished wall opening. Leading edge of door is fitted with a metal T bar to protect against attack with levers
 - Doors are fitted with one Euro profile mortice deadlock
- providing an exceptional degree of protection as standard. A number of other locking options are available, including emergency exit push bars. The doors are also designed to meet Equivalent RC 1-4 EN 1627 attack levels depending on door specification and locking solution chosen
- Customer Specified options like Door closers, magnetic locks, interlocking, customer specified locks, handles. Weather strip and stainless kick plates are available
 - Threshold of door is flush fitting as standard but for higher attack and blast doors then additional threshold rebate is required
 - Optional Fire resistant door infill to provide certified 2 hour fire resistance in addition to the standard security features

GUNNEBO®

Gunnebo ARMOUR Plus


Technical Information - single door

Model	Lock	Wall opening Height (mm)	Wall opening Width (mm)	Clearance 180° Height (mm)	Clearance 180° Width (mm)	Vision panel opening Height (mm)	Vision panel opening Width (mm)	Weight (kg)
G1/FB2 (9mm) security door	1KL	2100	950	2020	800	500	250	104
G2/FB3 (CP92) security door	1KL	2100	950	2020	800	500	250	125
G3/FB4-FB6 (AK47) security door	1KL	2100	950	2020	800	500	250	218


Custom sizes to order

Door openings

Hinge side and door opening to be specified when ordering



Doors available in left-hand or right-hand, inward or outward opening.
Arrow indicating attack side and direction of view
Left hand opening out



Doors available in left-hand or right-hand, inward or outward opening.
Arrow indicating attack side and direction of view
Right hand opening out

Hinge

Continuous full height hinge as standard.
Stainless bullet hinges offered as an option

Finish

Powder coated frame and door as standard.
Special colours are available if specified

Installation

Gunnebo is able to provide full installation if required. It is recommended that doors open outwards against the line of attack. Inward opening is available if required

Contact information

Telephone: +27 (0)11 878 2300
Email: info.africa@gunnebo.com
Website: www.gunnebo.africa



Take advantage of our knowledge
www.GunneboSafeStorage.com

GUNNEBO[®]