


## EXPOSED ACOUSTIC CEILING SYSTEM - EA1925\_1

Specifications are NOT PROJECT SPECIFIC and need to be approved by a project professional before use to ensure that they meet with the specific project requirements. SPECIFICATIONS NOT TO BE MODIFIED to suite without approval. **SPECIFICATIONS FOR INFORMATION ONLY.** The specification should be read in conjunction with Saint-Gobain current literature available on [www.gyproc.co.za](http://www.gyproc.co.za).

### Acoustic Ceiling System: Isover Cineplex® 40 mm - 600 mm x 600 mm Gypframe® D38FR suspended with Gyproc Hanger Strap 19 mm or Gyproc Suspension Wire

	(aw)Absorption Coefficient/ NRC/Absorption Class -(inclusive of insulation)	Board/ Tile size (mm)	Soffit Type	Finish
Not Applicable	_ / 0.8 - 0.9 / B	600 x 600	Concrete Flat slab	Ceiling Tiles

### System Overview

Lay Isover Cineplex® tiles (Size: 600 mm x 600 mm. Thickness: 40 mm) into the framework. Install Gypframe® D38FR Main Tees (Locally manufactured, recycled content, ISO 9001 & 14001 certification) at 1200 mm centres. Suspend Main Tee using Gyproc Hanger Strap/ Gyproc Suspension Wire fixed to Main Tee web using 2 steel pop-rivets or one Gyproc Wafer-Head Tek screw. Hangers to be at maximum 400 mm from perimeter wall. Install Gypframe® D38FR Cross Tee (1200 mm long) (Locally manufactured, recycled content, ISO 9001 & 14001 certification) at 600 mm c/c to create a 1200 mm x 600 mm ceiling grid. Install Gypframe® D38FR Cross Tee (600 mm long) (Locally manufactured, recycled content, ISO 9001 & 14001 certification) into the 1200 mm long cross tee to create a 600 mm x 600 mm ceiling grid. Install Gyproc Hold down clips per tile in areas susceptible to draught (2x per 1200 mm Cross Tee). Perimeter - Fix Gyproc M6 Wall Angle (locally manufactured) to the wall using fixings at 300 mm centres. Fix Main Tee's to the wall using Gyproc Angle Cleats to ensure straight grid and stability.

### System Information

Climatic zone	1	2	3	4	5	6
Isover Aerolite® thickness (mm)	<b>135</b>	<b>135</b>	<b>100</b>	<b>135</b>	<b>100</b>	<b>135</b>
R-Value of Aerolite®	3.38	3.38	2.5	3.38	2.5	3.38
Min. required total R-value	3.7	3.2	2.7	3.7	2.7	3.5

Where required, for improved thermal and acoustic performance, lay Isover insulation (locally manufactured, non-combustible to SANS 10177-5, SABS Mark) onto the ceiling.

Thickness: 100 mm/ 135 mm (according to climatic zone, see table above).

- Isover **Cavitybatt**: Thickness – 51 mm/ 63 mm/ 102 mm available.
- Isover **Factoryboard/ Factorylite**.

For improved acoustics, install Isover **Energylite**, Thickness – 25 mm/ 40 mm/ 50 mm available.

Details shown are subject to accuracy of information provided to Saint-Gobain at the time the drawings were originally requested. No duty of care is owed to the recipient or any other third party and Saint-Gobain does not accept any liability in respect of details shown. This Saint-Gobain system detail must not be used without a complete evaluation by owner's design professional to verify the suitability of it's use with your specific application. **The detail should be read in conjunction with Saint-Gobain current literature. Refer to literature and clauses at <https://www.gyproc.co.za/>.**