

1. *Steel Brander:*
 - Product: Donn steel brander.
 - Donn steel brander shall be spaced at maximum 400mm centres.
2. *Suspension:*
 - Product: Donn suspension brackets.
 - Fix Donn suspension brackets to joist/tie beam at 400mm centres using one line of 2 x Gyproc grabber screws. Maximum joist/tie beam spacing is 1200mm.
 - Donn steel brander is clipped-onto the Donn suspension brackets. Brander are joined using brander joiners.
3. *Wall Angle:*
 - Product: Donn galvanised steel angle 25mm x 25mm.
 - Fix Donn galvanised steel angle 25mm x 25mm as a perimeter angle; fixed to the wall using proprietary fixings at 300mm centres.
 - Fix Donn steel brander to the perimeter angle.
4. *Ceiling Board:*
 - Product: 1 layer Gyproc RhinoBoard 6.4mm.
 - Gyproc RhinoBoard 6.4mm is fixed to Donn steel brander with the longer side of the board running perpendicular to the direction of the brander.
 - Fix Gyproc RhinoBoard 6.4mm to Donn steel brander using Gyproc sharp point screws 25mm at maximum 150mm centres. All joints should be staggered.
 - Apply Donn M-Strip to the joints.
 - Spot/cover all the screw heads using Gyproc RhinoGlide.
5. *Cornice:*
 - Product : Gyproc Cove cornice 75mm/125mm or Gyproc RhinoArt cornice.
 - Install Gyproc Cove cornice using Gyproc RhinoBed or Gyproc RhinoArt cornice using Gyproc RhinoArt adhesive, between the ceiling perimeter and the wall.
6. *Insulation*
 - Where required, for improved thermal and acoustic performance, lay Isover insulation onto the ceiling.
 - Thickness= 100mm/115mm/135mm (according to climatic zone, see table below.)

SANS 10400XA and SANS 204 requirements for ceiling insulation.

Climatic zone	1	2	3	4	5	6
Isover Aerolite thickness (mm)	135	115	100	135	100	135
R-value of Aerolite	3.38	2.88	2.5	3.38	2.5	3.38
Min. required total R-value	3.7	3.2	2.7	3.7	2.7	3.5



GypCeil Classic M-Strip (steel branderling)


7. *Finish:*

- Paint in accordance with the manufacturer's specification.

NB-To be read with General Ceiling Design Guidelines documents.



GypCeil Classic with M-Strip



Details shown are subject to accuracy of information provided to Saint-Gobain at the time the drawings was originally requested.
 No duty of care is owed to the recipient or any other third party and Saint-Gobain does not accept any liability in respect of details shown.
 This Saint-Gobain System Detail must not be used without a complete evaluation by owner's design professional to verify the suitability of its use with your specific application.
 The detail should be read in conjunction with Saint-Gobain current literature available on www.gyproc.co.za.

DRAWING NO.	GC-CLASSIC M-STRIP	
NOTES	To be read in conjunction with project specifications	
SCALE	not to scale	