

Technical data sheet

EasyLite multipurpose plaster 20Kg.

Description

EasyLite is a gypsum plaster-based product designed to level uneven internal surfaces and to smooth levelled surfaces for a superior and smooth finished result.

Uses

This product can be used directly on the following substrates:

- Sand and cement plastered walls
- Gypsum-based plasterboards
- Concrete slabs and soffit
- Brick surfaces

Caution

EasyLite should not be applied in areas where high moisture levels occur, such as bathrooms and laundries.

Please note the following:

- EasyLite is for internal use only
- It is not made for human consumption
- Keep out of reach of children
- Use PPE for protection

Application instructions

1. Mix the content of 1 bag with 12 Litres of water in a flexible bucket; please use clean drinkable water.
2. For the best results, use a mechanical mixing paddle.
3. Thickness of application can vary between 3mm-75mm.
4. Surfaces need to be cleaned before applying EasyLite.
5. Apply Fibre tape to the joints and cover the joints with EasyLite.
6. Apply the product onto the pre-jointed surface at a minimum thickness of 3mm. Jointing with the same batch before skim application.
7. Apply a thin skim layer of plaster to the required area.
8. More layers may be applied afterwards, whilst the product is still wet.
9. Run the surface over with the first trowel to level the applied area.
10. As the product begins to set, apply a second trowel to the total surface to remove the trowel lines.
11. Run a final trowel over the hardened surface, applying water conservatively to achieve a smooth surface.
12. Do not sand the plastered surface.
13. When plastering pre-painted surfaces:
 1. test background to make sure there is no delamination;
 2. clean background;
 3. apply 1 coat of EasyGrip bonding agent;
 4. once the surface has dried up completely, apply EasyLite.

Technical data sheet (Continued)

EasyLite multipurpose plaster 20Kg.

Finishing suggestions

EasyLite plaster needs to be primed before applying paint, please consult your painting supplier for a suitable plaster primer. Variance from the application instructions will result in dust or residue on the surface after set and dry time is completed, applying a primer will assist against potential delamination of finishing materials, due to deviance from the application and cleaning instructions. It is important that you adhere to the application instructions as stipulated.

Benefits

- Pre-treatment of joints and screws is not required.
- Total coverage of plasterboard provides a holistically smooth surface.
- Skimmed surfaces are highly resistant to impact and scratches.
- Skimmed surfaces can be painted directly after the product is set and dry.
- No sanding required.
- Surfaces to be clean of dust and oil residue before application.
- Don't apply when the temperature is below freezing.
- Application of epoxy paint is not recommended.
- Please consult your paint manufacturing company for recommendations on plaster primers and paint.

Storage

Store EasyLite inside, on a level surface, off the floor, in a dry place protected from the weather.

EasyLite tool requirements

- Flexible container for mixing
- Hand mixer or machine mixer
- Hand hawk
- Rubber float
- Steel trowel
- Block brush
- PPE