PAINTCOR

SUPREME QUALITY Since 1986

2020 Revision

PLASTERBOND

Description and Application

CATEGORY

Primer / Cement Enhancer

DESCRIPTION

PlasterBond is a specially formulated latex which has been developed to promote the adhesion between new plaster and the surface to which the plaster is being applied.

FEATURES

- PlasterBond is Alkali-resistant
- Good binding power

AREAS OF USE

- Incorporation into cement mixtures
- As a key coat for new plaster work

SURFACE PREPARATION AND APPLICATION

- 1. Prepare the surface for re-plastering.
- 2. Remove all dirt and dust from the surface to be plastered.
- 3. Ensure the surface is dry.
- 4. Apply 1 coat of Paintcor's PlasterBond.
- 5. Allow sufficient time to dry. The product will turn clear on drying.
- 6. While PlasterBond is still tacky, (just after drying) apply the new plaster.

Note: PlasterBond can be added to cement mixtures to improve their properties (adhesion, water resistance and strength



RSA

[Type here] PAINTCOR

SUPREME QUALITY Since 1986

APPLICATION EQUIPMENT

Apply by Brush or Roller

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children.

www.paintcor.co.za