

## Econogrid

Pelican Systems Econogrid Exposed Tee Grid System - 1200 x 600mm System

Supply and install 3600mm Econogrid main tees at 1200mm centres in one direction and 1200mm Econogrid cross tees at 600mm centres perpendicular to the main tees. Main tees are to be suspended at 1200mm centres with the appropriate hangers

Pelican Systems Econogrid Exposed Tee Grid System - 600 x 600mm System

Supply and install 3600mm Econogrid main tees at 1200mm centres in one direction and 1200mm Econogrid cross tees at 600mm centres perpendicular to the main tees. Install 600mm Econogrid cross tees between the 1200mm cross tees to form a 600 x 600mm grid. Main tees are to be suspended at 1200mm centres with the appropriate hangers

**\*NOTE:** All ceilings should be installed in accordance with the current code of practice for ceiling installation adopted by the South African Building Interior System Association (SABISA). Care should be taken to ensure that the fixing used for the suspension points should be able to support a safety factor of three times the design load of the ceiling. Suspended ceilings are not designed to take the weight of services personnel walking around on its surface. The ceiling erection should take place at a later stage in the building contract when the area is clean and there is less likelihood of damage from other trades and exposure to the elements.



KZN Head Office: (031) 563 7307  
[www.pelican.co.za](http://www.pelican.co.za)  
[info@pelican.co.za](mailto:info@pelican.co.za)

Find this specification on



 ceiling systems  partitioning systems  opening systems  flooring systems