

8mm JUMBO Multi-Purpose Ceiling Board

1. Grid System:

Supply and install 3,600mm JUMBO main tees at 1,000mm centres in one direction and 1,000mm JUMBO cross tees at 500mm centres perpendicular to main tees. Main tees to be suspended at 1,200mm centres by means of a 25 x 25 x 0.6mm galvanised steel angle fixed to bulb of main tee with wafer tek screws and to slab, steel purlins or timber trusses.

- a) Fix 8.0mm thick JUMBO Plasterboard to underside of grid system with tapered edges of board facing down with 25mm JUMBO drywall screws at 150mm centres. Apply 50mm JUMBO tape to all joints and finish the entire ceiling with 3-5mm JUMBO Skimming Plaster.
- b) Fix 8.0mm thick JUMBO Plasterboard to underside of grid system with tapered edges of board facing down with 25mm JUMBO drywall screws at 150mm centres. Apply 50mm JUMBO tape to all joints and finish the joints and screw heads with JUMBO Jointing Plaster.
- c) Fix 8.0mm thick JUMBO Plasterboard to underside of grid system with tapered edges of board facing up with 25mm JUMBO drywall screws at 150mm centres. ALL joints to be covered with JUMBO PVC H-profile.

2. Steel Brandering System (timber can be used)

Supply and install JUMBO steel Brandering at 500mm centres in one direction fixed to timber trusses at 1,200mm centres with galvanised JUMBO suspension bracket.

- a) Fix 8.0mm thick JUMBO Plasterboard to underside of Brandering with tapered edges of board facing down with 25mm JUMBO drywall screws at 150mm centres. Apply 50mm JUMBO tape to all joints and finish the entire ceiling with 3-5mm JUMBO Skimming Plaster.
- b) Fix 8.0mm thick JUMBO Plasterboard to underside of Brandering with tapered edges of board facing down with 25mm JUMBO drywall screws at 150mm centres. Apply 50mm JUMBO tape to all joints and finish the joints and screw heads with JUMBO Jointing Plaster.
- c) Fix 8.0mm thick JUMBO Plasterboard to underside of Brandering with tapered edges of board facing up with 25mm JUMBO drywall screws at 150mm centres. ALL joints to be covered with JUMBO PVC H-profile.

*NOTE: Ceilings to be installed by an approved specialist and in accordance with the SABISA (South African Building Interior Systems Association) installation guidelines.



KZN Head Office: (031) 563 7307
www.pelican.co.za
info@pelican.co.za

Find this specification on

