



PRODUCT DETAILS

BRASS VALVE / EPDM WASHER BRASS VALVE WITH EPDM RUBBER WASHER

AERATOR ; NEOPERL

S-CONNECTORS Extended S-connectors for easier installation & retro fit

TECHNICAL SPECIFICATIONS

FLOW RATE 20L/ MINUTE @ 3 BAR

SABS APPROVED*

BRASS GRADE DZR (dezincification resistant brass) Cz132

CHROME PLATING 200 HOUR SALT SPRAYED FINISH (Ni: 7 μ & Cr: 0.2 μ) THICKNESS

BSP THREADS 15mm MALE S-CON THREADS / 3/4" FEMALE MIXER THREADS

CLEANING INSTRUCTIONS

1. Avoid cleaning agents containing ingredients, such as chlorine bleach, formic acid, acetic or Hydrochloric acid.
2. Wipe all surfaces using a soft unabrasive cloth, with warm soapy water.



10 YEAR GUARANTEE

WWW.PLUMBLINK.CO.ZA

Plumblink tries its best to ensure that the information given on our website is accurate. Although, we cannot guarantee this for certain, and accept no liability for any information.

HYDRUS SINK MIXER WALL-TYPE

031462

SPECIFICATION SHEET

