



LYRA WALL TYPE SINK MIXER

034150

SPECIFICATION SHEET

PRODUCT DETAILS

CARTRIDGE HIGH QUALITY SUPERIOR SPEC CARTRIDGE

NEOPERL AERATOR EASY FLOW AERATOR

S-CONNECTORS STAINLESS STEEL S-CONNECTORS FOR
EASIER INSTALLATION

TECHNICAL SPECIFICATIONS



FLOW RATE 15L/ MINUTE @ 300Kpa

SABS APPROVED*

BRASS GRADE DZR (dezincification resistant brass) Cz132

CHROME PLATING 200 HOUR SALT SPRAYED FINISH (Ni: 7μ
& Cr: 0.2μ) THICKNESS

BSP THREADS 15mm MALE S-CON THREADS / 3/4" FEMALE
MIXER THREADS



CLEANING INSTRUCTIONS

1. Avoid cleaning agents containing ingredients, such as chlorine bleach, formic acid, acetic or Hydrochloric acid.
2. Wipe all surfaces using a soft unabrasive cloth, with warm soapy water.



5 YEAR WARRANTY

WWW.PLUMBLINK.CO.ZA

Plumblink tries its best to ensure that the information given on our website is accurate. Although, we cannot guarantee this for certain, and accept no liability for any information.