## Seagual Technical Data Sheet - BuddyClips



## **Section 5: Pipe Anchors & Fixings**

#### 5.2 BuddyClips 20mm & 25mm

5.2.1 Definition: Electrical Conduit Anchors.

#### 5.2.2 Product introduction:

The 'BuddyClip', is a unique electrical conduit anchor designed with its primary function to anchor and hold conduit pipe in a selected position.

The 'BuddyClips' are available in two sizes: 20mm and 25mm and are manufactured in White UV stabilised Polypropylene to add and promote a longer lifespan.

BuddyClip is a registered Trademark.

### 5.2.3 Key Benefits:

- a. UV stabilisers are added to promote a longer lifespan.
- b. Easy to install with a quality finish used on conduit pipe.
- c. Supplied with 6mm x 70mm nail-in-anchors which can unscrew for maintenance (can be used with any other 6mm x70mm screw as long as it can be removed for maintenance purposes).
- d. Ideal for securing electrical conduit pipe work anywhere with a zero-breakage rate.
- e. The 'BuddyClips' can be painted when used on external walls.

#### 5.2.4 Applications:

Used to secure and hold 20mm and 25mm electrical conduit pipes anywhere in a desired and selected position for example on wooden, concrete, brick and plastered surfaces.

## 5.2.5 Installation: (New installation)

- a. Read instructions and check that all components are supplied.
- b. Once the final position for the installation of the selected pipe has been established, measure and mark out the desired intervals of the 'BuddyClips' in accordance with the recommended spec of the pipe being used. Ensure that the selected intervals are plumb and level.
- c. Drill the 6mm hole with the correct drill bit for the application and to the correct depth. Place 'BuddyClips' onto the 20mm or 25mm electrical conduit pipe work then fit the supplied nail-inanchor and position conduit, then drive nail home while taking care NOT to damage the surround of the pipe or use a 70mm pozzi screw and fasten with screwdriver.

Congratulations you are a proud installer/owner of a 'High Quality', Seaqual product.

#### 5.2.6 Maintenance:

BuddyClips do not require maintenance once installed correctly.

## 5.2.7 BuddyClip Product Data

## 5.2.7.1 Table A:

ELEMENT	20mm	25mm
Weight / unit	7g	11g
Length	35mm	40mm
Width	15mm	15mm
Height	25mm	30mm
Inner Diameter	20mm	25mm
Supplied in Packets of 10 units	033105	033106
Material	Polypropylene (PP) UV Stabilised	
Additives	Colourant + UV Stabiliser	
Estimated Lifespan	+15 years	

 Doc No. ESM-SAM-102
 Issue Date: 2013/11/30
 Approved by: T. Cloete

 Rev No: 3
 Rev Date: 12/07/2021
 Page 1 of 2

# Seaqual Technical Data Sheet - BuddyClips



Standard Colours	White
Additional Colours (MTO)	As requested,

## 5.1.7.2 BuddyClip Product Specification & Order Codes Data

Units / Bag	20mm	25mm
10	033105	033106

#### 5.1.8 Terms & Condition of Product Warranty


On the conditions appearing below Seaqual warrants that the products it manufactures are free from defect for the periods set out in Warranty Period column for use in the manner described in the Application column.


Seaquals range of products are made from different types of plastics which determines their longevity. Research into the various plastics Seaqual uses indicates that the life expectancy of the various materials ranges from 50 to 100 years and for this reason Seaqual can confidently offer the lengthy warranties set out in the schedule. Under this warranty Seaqual undertakes to replace any item that does not last for the period of the warranty provided that the following conditions are met:-

- 5.1.8.1. Any failure of the product has not been caused by abuse of the Product;
- 5.1.8.2. The Product has been correctly installed in terms of the Installation Instructions provided by Seaqual;
- 5.1.8.3. In the case of floor drains / full-bores / sumps no corrosive liquids have been poured into or through the Product;
- 5.1.8.4. The purchase receipt pertaining to the purchase of the Product or details of where purchased are provided;
- 5.1.8.5. The claim is submitted on line to the Technical Director, Seaqual (Pty) Ltd at tech@seaqual.co.za or in writing to Seaqual at 5 Fechter Street, Knysna Western Cape:
- 5.1.8.6. Photographs of the defective Product are submitted with the claim, Seaqual reserving the right to call for the defective Product itself should the photographs be insufficient evidence of any alleged defect (this within Seaquals sole discretion);
- 5.1.8.7. The claim is limited to the actual replacement of any defective product at no cost to the purchaser/claimant and does not cover any consequential losses that the purchaser may contend he or she has suffered.

NOTE: The 2 year warranty excludes any component of the product which is not manufactured by Seaqual such as the rubber seals, nuts and bolts. These items carry a 2 year warranty against manufacturer defects. Please note that Seaqual cannot be held responsible for inaccurate installation processes.

## 5.1.9 Drawings







 Doc No. ESM-SAM-102
 Issue Date: 2013/11/30
 Approved by: T. Cloete

 Rev No: 3
 Rev Date: 12/07/2021
 Page 2 of 2