Seaqual Technical Data Sheet - Ceiling Saver



Section 6 - Long Term Cost Saving Devices

6.1 **Ceiling Saver**

6.1.1 **Definition: Cost Saving Device for Geysers**

6.1.2 **Product introduction:**

The Ceiling Savers are unique little devices that are installed over the vacuum breakers of the geyser.

Vacuum breakers can fail and if they do, there is no provision to lead water outside of the home. In the event of a vacuum breaker failure, the ceiling saver directs the flow of water safely through the overflow pipe and discharges the water outside the home, thereby preventing flood damage within. Use Ceiling Savers on both your inflow and outflow water pipes for best results.

The Ceiling Saver has a 22mm Ø bottom outlet with a rubber seal to prevent leaks and 1x 15mm converter is provided for.

6.1.3 **Key Benefits:**

- a. Prevents damage to property should a vacuum breaker fail.
- b. Cost effective product.
- c. Made from durable Polypropylene.
- d. Easy and quick to install.

6.1.4 **Applications:**

Installation of the Ceiling Saver on both inlet & outlet pipes on all geysers & must be installed over vacuum breakers of the geyser.

6.1.5 Installation:

- 6.1.5.1 Read instructions and check that all components are supplied.
- 6.1.5.2 Unscrew the stoppers on the ceiling saver and slide onto the pipe.
- 6.1.5.3 Insert & attach the vacuum breaker to the pipe.
- Connect the fail-safe outlet pipe and diver to exterior of the building. 6.1.5.4
- Screw on top tightly 6.1.5.5
- A 15mm stopper is provided for use where 15mm copper pipe has been specified. 6.1.5.6

Congratulations you are a proud installer/owner of another High Quality Seagual product.

6.1.7 **Maintenance Required:**

No maintenance to actual product is required.

6.1.8 **Ceiling Saver Product Data**

Product Name	Ceiling Saver
Product Code	097780
Product Image	
Total Height	143mm
Total Width at widest point	118mm

Doc no.: ESM-SAM-102 Date added: 01/10/2013 Approved by: T. Cloete Rev. Date: 18/06/2021

Rev no: 3

Seaqual Technical Data Sheet - Ceiling Saver



Bottom inlet ID	22mm
Side Outlet ID	22mm
Total Weight of product	0.145kg
Other Outlets available	Yes – 1x 15mm converter is provided for
Other colours available	No
Fail Safe Feature	Rubber seals
Product Warranty	2 year (product warranted by Principal Plastics)
Product Application	Long term cost saving device to be installed on internal geysers.
Design Data	
Auto Cad	Yes
Revit	Yes
Packaging Data	
Packaging Info	Clear bag & sticker
Units / Outer Box	30
Total weight of Outer Box	5.35kg
Outer Box Dimensions in mm	520mm x 280mm x 620mm
Product Barcode:	6001651048766
Outer Box Barcode	16001651048763

6.1.9 **Terms & Conditions of Product Warranty**

On the conditions appearing below Seaqual warrants that the products it manufactures are free from defect for the periods set out in Warranty Period column for use in the manner described in the Application column.

Seaquals range of products are made from different types of plastics which determines their longevity. Research into the various plastics Seagual uses indicates that the life expectancy of the various materials ranges from 50 to 100 years and for this reason Seaqual can confidently offer the lengthy warranties set out in the schedule. Under this warranty Seaqual undertakes to replace any item that does not last for the period of the warranty provided that the following conditions are met:-

- 6.1.9.1 Any failure of the product has not been caused by abuse of the Product:
- 6.1.9.2 The Product has been correctly installed in terms of the Installation Instructions provided by Seagual:
- 6.1.9.3 In the case of floor drains / full-bores / sumps no corrosive liquids have been poured into or through the Product;
- 6.1.9.4 The purchase receipt pertaining to the purchase of the Product or details of where purchased are provided;
- 6.1.9.5 The claim is submitted on line to the Technical Director, Seagual (Pty) Ltd at tech@seaqual.co.za or in writing to Seaqual at 5 Fechter Street, Knysna Western Cape:
- 6.1.9.6 Photographs of the defective Product are submitted with the claim, Seagual reserving the right to call for the defective Product itself should the photographs be insufficient
- 6.1.9.7 evidence of any alleged defect (this within Seaquals sole discretion);

The claim is limited to the actual replacement of any defective product at no cost to the purchaser/claimant and does not cover any consequential losses that the purchaser may contend he or she has suffered.

NOTE: The 2 year warranty excludes any component of the product which is not manufactured by Seagual such as the rubber seals, nuts and bolts. These items carry a 2 year warranty against manufacturer defects. Please note that Seagual cannot be held responsible for inaccurate installation processes.

Doc no.: ESM-SAM-102 Date added: 01/10/2013 Approved by: T. Cloete Rev. Date: 18/06/2021


Rev no: 3

Seaqual Technical Data Sheet – Ceiling Saver



6.1.11 Drawings / Product Images

CAD & Revit drawings available in writing to: tech@seaqual.co.za



Typical installation of Ceiling Saver on a Geyser:



6.1.12 Certifications

Seaqual (Pty) Ltd is ISO9001:2015 Certified.

WHOLLY MANUFACTURED IN SOUTH AFRICA - Tariff Heading / HS Code 3922.90.90

These products are available through most Plumbing Merchants within South Africa and can be viewed on our website: http://www.seaqual.co.za.

Request for quotations or placing of orders can be sent to orders@seaqual.co.za

Doc no.: ESM-SAM-102 Date added: 01/10/2013 Approved by: T. Cloete Rev. Date: 18/06/2021

Rev no: 3