



FAST WALLSKIM (SPRAY-ON)

PRODUCT DATA SHEET

DATE: MAY 2018

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS



Product description

FAST WALLSKIM (SPRAY-ON) is a flexible ready for use high build skimming/plastering compound to fill cracks and other irregularities to give a smooth professional - plastered finish to walls and other substrates (E.g. Dry walling). Fast Wall Skim requires no mixing with water, it is ready for use. It requires no priming with bonding liquid. Ready to use for spray application.

Intended Uses

For interior and exterior use to fill and repair cracks, holes, plaster imperfections and blemishes to a smooth and even finish.

Features & Benefits

- 12-year guarantee
- Provides superior plaster finish
- Tough and durable
- Alkali resistant
- Excellent adhesion
- No primer or bonding liquid required before painting
- Ready mixed – saving you time and money
- Easy application

Product Information

Type	Aggregate gypsum acrylic hybrid
Appearance	Smooth paste
Colours	Off-white
Flash Point	Non-flammable
	Non-toxic
Spread Rate:	0,5-1,5kg/m ² depending on substrate conditions. Apply in layer thickness of approximately 1mm.

Practical spreading rate: The practical spreading rate will vary depending on the porosity and profile of the substrate, as well as the application technique and tools used.

Cautions

Only for interior use.

Surface Preparation

1. Remove protruding cement spatter using a scraper or sandpaper.
2. Ensure that the surface is in a dry and sound condition – free from dust or any loose particles.
3. On powdery, unsound surfaces – apply bonding liquid.
4. Previously painted surfaces must be sanded down to create a key for adhesion.

Application Details

Mixing Method	Stir thoroughly with a flat paddle Steel trowel or spray machine
Cleaning	Water
Drying time	12 Hours
Topcoat	Allow to dry 12 hours before painting with water-based paints Allow to dry 48 hours before painting with solvent based enamel paints

1. Apply WALLSKIM with a special spray application machine.
2. WALLSKIM is normally applied with a spreading rate of 0,5-1,5kg/m² depending on substrate conditions. Apply in layer thickness of approximately 1mm.
3. Allow to dry 2-3 hours. Sand lightly with a light to medium grade sandpaper and wipe off dust properly.

FAST

WALLSKIM (SPRAY-ON)

INTERIOR & EXTERIOR



4. Apply a second coat if necessary. WALLSKIM can be floated or polished with a trowel.
5. After final coat application allow WALLSKIM to dry until it starts to firm up and set (product will lighten in colour), sprinkle or flick water onto surface with a brush and float or polish in a light circular motion.
6. Allow to dry 12 hours (overnight) before painting with a water-based paint.
7. Allow to dry 48 hours before painting with a solvent based enamel paint.

Storage & Packaging

Store away from direct sun, heat and severe cold.

Packaging: 35kg (20ℓ).

Safety Precautions

Keep out of reach of children.

Ensure good ventilation during application and drying.

In case of skin contact, wash with soap and water or a recognised skin cleanser.

Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.

Harmful if swallowed. Do not induce vomiting. Drink plenty of water. Seek medical attention.

Refer to Material Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest Technical Data Sheet is being used.