



Valdisole 704-706 6th Street, Wynberg, Sandton, 2090
info@versuspaint.co.za | T: (011) 885 3136 | F: (011) 885 1719
www.versuspaint.co.za | www.paintwithapurpose.co.za | www.specifications.co.za



Versus Pink Wood Primer (VPWP) Data sheet no 23-2015

PRODUCT DESCRIPTION:

A solvent based penetrating wood primer for interior and exterior surfaces.

USES:

A general purpose primer for wood

FEATURES:

- Economical and easy to apply.
- Good adhesion.
- Very good protection.

PRODUCT INFORMATION:

- Type: Alkyd.
- Appearance: Matt/low sheen.
- Colors: White and Pink.
- Solids: 63-64% by mass.
- Specific Gravity: 1.35 – 1.4.
- Viscosity (Sheen Cup): 30 -35 Secs.
- DFT/coat: Min 30µm Max 35µm.
- Flash Point: 35°C.

APPLICATION DETAILS:

- Mixing: Stir well before use.
- Method: Short nap mohair roller or brush.
- Thinning: Mineral Turpentine.
- Clean up: Mineral Turpentine.
- Spreading rate: 8 – 10m²/l depending on surface porosity and profile.
- Conditions: Avoid painting in wet or cold weather. Minimum temp 8° C
- Drying time: Touch dry 3 – 4 hours. Hard dry 16 – 18 hours at 25 degrees.
- Recoating time: 18 hours.

DISCLAIMER

The above information is given in good faith but without warranty due to the fact that the methods of application, location and condition of the substrates being coated are beyond our control.

SURFACE PREPARATION:

- New Surfaces must be sound, clean and dry (moisture content below 15%) before priming.
- Ensure to prime the end grain to avoid moisture penetration.
- Previously varnished surfaces.
- For surfaces in poor condition: Strip down and patch prime.
- Surfaces in good condition do not require priming.

STORAGE:

- Keep containers properly sealed.
- Store away from direct heat, sun and severe cold.

PACKAGING:

- 1 Liter – 5 Litres – 20 Litres.

PRECAUTIONS:

- Detailed safety information: refers to the material safety data sheet for this product.
- Not suitable on sealed or varnished surfaces.
- Do not apply on wet or damp surfaces.
- Do not paint in wet or cold weather. (Minimum 5°C.)
- Drying times will be extended during wet or cold weather conditions.